RWTH Aachen

Department of Computer Science
Technical Report

The Complexity of Deciding a Behavioural Pseudometric on Probabilistic Automata

Hongfei Fu

ISSN 0935–3232 · Aachener Informatik-Berichte · AIB-2011-26

RWTH Aachen · Department of Computer Science · December 2011

The publications of the Department of Computer Science of *RWTH Aachen University* are in general accessible through the World Wide Web.

http://aib.informatik.rwth-aachen.de/

The Complexity of Deciding a Behavioural Pseudometric on Probabilistic Automata

Hongfei Fu

Lehrstuhl für Informatik II
RWTH Aachen, Germany
Email: hongfeifu@informatik.rwth-aachen.de

Abstract. In this paper we study the complexity of computing a behavioural pseudometric on Segala's probabilistic automata. The pseudometric concerned here stems from a real-valued logic (by Desharnais *et al*) and does not discount the future. We show that the problem whether the pseudometric between two states of a finite probabilistic automata is under a given threshold lies in the intersection of NP and coNP. This result significantly improves the previous PSPACE upperbound (by e.g. van Breugel *et al*).

1 Introduction

In recent years, probabilistic behavioural equivalences have been extensively studied. Many equivalences such as probabilistic bisimulation [LS91,SL95] and probabilistic simulation [JL91,SL95] have been established. And many efficient algorithms have been proposed for these equivalences [BEMC00,CS02]. Here we focus on probabilistic bisimulation. Generally, probabilistic bisimulation is a class of formal notions judging whether two probabilistic systems are behaviourally "equivalent". In practical problems, they are often used to compare an implementation of a system with the specification of the system, where both the implementation and the specification are modeled by formal probabilistic systems. Furthermore, one can also tackle the state explosion problem by reducing a large probabilistic system to its quotient system w.r.t probabilistic bisimulation. This is because the quotient system is often PCTL- or PCTL*-equivalent to the original one [ASB95,SL95].

However, the notion of probabilistic bisimulation relies on exact probability values and a slight variation of probability values will differentiate two originally equivalent probabilistic systems. In this sense, this notion is not robust. This is drastically the case when a probabilistic system contains physical objects (such as a wire) whose probability values are based on experimental results. In this case, the probabilistic values should not be treated as "exact values". Even in pure theoretical probabilistic models where probability values are indeed exact, an implementation of the model may still contain probability values which deviate slightly from their original counterparts. Thus, a notion of approximate bisimulation is really needed.

The notion of approximate bisimulation is first considered by Giacalone *et al* [GcJS90]. They defined a pseudometric over the states of a probabilistic transition system. This yields a smooth, quantitative notion of behavioural equivalence. A pseudometric differs from an ordinary metric in that different elements (i.e., states) can have distance 0. The distance between states, a real number between 0 and 1, can be used to express the similarity of the behaviour of the system

started in those states. The smaller the distance, the more alike the behaviour is. In particular, the distance between states is 0 if they are indistinguishable.

Then the study of approximate bisimulation is divided into two directions. One direction is through a study of real-valued logic where the main work is by Josée Desharnais *et al* [DGJP04]. The other is through a study of coalgebra representation of probabilistic transition systems where the main work is by Franck van Breugel *et al* [vBW01b]. They both defined a pseudometric for probabilistic systems where states with zero distance are probabilistic bisimilar [LS91]. Both of the two pseudometrics are classified into future-discounting (*abbr.* FD) and non-future-discounting (*abbr.* nFD) version. In the FD version, differences that appear in the future are discounted and contribute less to the value of the pseudometric. While in nFD version, differences that appear in the future contribute fully to the pseudometric. NFD pseudometrics seems to be a more natural extension of probabilistic bisimulation, as in [Pan09,vBSW07] it is shown that the nFD pseudometric [DGJP04] defined through a real-valued logic can be defined in a style similar to probabilistic bisimulation [LS91]. Also the notion of nFD pseudometrics is important to analyze systems that are expected to run forever. For FD version, efficient approximation algorithms have been obtained on finite-state systems [vBW01a]. However for nFD version, the best-known complexity upperbound (before this paper) is only PSPACE [vBSW07,CHL09].

In this paper, we consider the nFD pseudometric over finite probabilistic automata [SL95] which is an extension of the nFD ones defined in [Pan09,vBSW07]. We show that the problem whether the pseudometric between two given states is under a given threshold lies in $\mathsf{NP} \cap \mathsf{coNP}$, which significantly improves previous PSPACE upperbound [vBSW07,CHL09].

2 Preliminaries

2.1 Finite Probabilistic Automata

In this subsection we define the notion of "finite probabilistic automata", which corresponds exactly to Segala's "simple probabilistic automata" [SL95] in the finite setting.

Definition 1 (Probability Distribution). *Let S be a countable set. A function $\mu : S \to [0,1]$ is a* probability distribution *over S if $\sum_{s \in S} \mu(s) = 1$ and $\mu(s) \in \mathbb{Q}$ for all $s \in S$. We denote the set of probability distributions over S by $\mathcal{D}(S)$.*

Definition 2 (Finite Probabilistic Automata). *A* finite probabilistic automata *(finite PA) $\mathcal{T}$ is a tuple (S, Act, Ω) where*

- *S is a finite set of* states*;*
- *Act is a finite set of* actions*;*
- *$\Omega \subseteq S \times Act \times \mathcal{D}(S)$ is a finite set of* transitions*.*

We define $\mathrm{Act}^{\mathcal{T}}(s) := \{a \in Act \mid \exists \mu.(s,a,\mu) \in \Omega\}$ for each $s \in S$. We write $s \xrightarrow{a} \mu \in \Omega$ instead of $(s,a,\mu) \in \Omega$. We omit '$\mathcal{T}$' or 'Ω' in the notations above if the context is clear.

Finite probabilistic automata extend Markov Chains studied in [vBSW07,Pan09] in the sense that a Labeled Markov Chain can be deemed as a finite probabilistic automata where the transition relation Ω is a function from $S \times Act$ to $\mathcal{D}(S)$.

2.2 Polyhedra and Linear Programming

We introduce polyhedra and linear programming along [Sch10]. Given a real-valued vector b, we denote b^i to be the i-th entry of b.

Definition 3 (Polyhedra). *A subset $H \subseteq \mathbb{R}^n$ is a* halfspace *iff there is $h \in \mathbb{R}^n$ and $e \in \mathbb{R}$ such that $H = \{x \in \mathbb{R}^n \mid h^T x \leq e\}$. A subset $P \subseteq \mathbb{R}^n$ is a* polyhedron *iff it is the intersection of a finite number of halfspaces. Equivalently $P \subseteq \mathbb{R}^n$ is a polyhedron iff there is an $m \times n$ matrix A and a vector $b \in \mathbb{R}^m$ such that $P = \{x \in \mathbb{R}^n \mid Ax \leq b\}$, where "$Ax \leq b$" is an abbreviation for "$(Ax)^i \leq b^i$ for all $1 \leq i \leq m$".*

Remark 1. Informally, a polyhedron is a finite intersection of constraints of the form $h^T x \leq e$. Note that constraints such as $h^T x \geq e$ or $h^T x = e$ are covered, since "$h^T x \geq e$" can be rewritten as "$(-h)^T x \leq -e$" and "$h^T x = e$" is equivalent to "$h^T x \leq e$ and $h^T x \geq e$".

An important concept to characterize polyhedra is the notion of vertices.

Definition 4 (Vertex). *Let P be a polyhedron. A point $z \in P$ is a* vertex *iff there does not exist points $x, y \in P$ and $\lambda \in [0,1]$ such that $x \neq z$, $y \neq z$ and $z = \lambda \cdot x + (1-\lambda) \cdot y$.*

The following theorem states that vertices of a polyhedron can be characterized by full-rank rows of the specifying matrix, whose proof can be found in [Sch10, Theorem 2.2].

Theorem 1. *Let $P = \{x \in \mathbb{R}^n \mid Ax \leq b\}$ be a polyhedron in $\mathbb{R}^n$ and $z \in P$. Define the matrix A_z to be the submatrix of A consisting of all the row vectors h_i of A for which $h_i z = b^i$. Then z is a vertex of P iff $\operatorname{rank}(A_z) = n$.*

Definition 5 (Linear Programming). *A* linear programming problem *(LP) is specified by its type as well as an $m \times n$ matrix A and two vectors $b \in \mathbb{R}^m, c \in \mathbb{R}^n$. There are two types of LP's: MAX-LP and MIN-LP, whose forms are as follows:*

MAX-LP	*MIN-LP*
maximize $c^T x$	*minimize* $c^T x$
subject to $Ax \leq b$	*subject to* $Ax \leq b$

Let Γ be an LP (either a MAX-LP or a MIN-LP) as above. The aim is to compute the optimal value *(denoted $\mathrm{OpV}(\Gamma)$) of Γ, which is defined as the maximum (for MAX-LP) or minimum value (for MIN-LP) of the set $\{c^T x \mid x \in \mathbb{R}^n \text{ and } Ax \leq b\}$. The set of* feasible solutions *of Γ, denoted $\mathrm{Poly}(\Gamma)$, is defined as the polyhedron $\{x \in \mathbb{R}^n \mid Ax \leq b\}$. The set of* optimal solutions *of Γ, denoted $\mathrm{OpS}(\Gamma)$, is defined as $\{x \in \mathrm{Poly}(\Gamma) \mid c^T x = \mathrm{OpV}(\Gamma)\}$.*

Note that the maximum or minimum value can be reached if the supremum or infimum is finite, since $\mathrm{Poly}(\Gamma)$ is a closed set and $x \mapsto c^T x$ is a continuous function.

The following theorem clarifies the relationship between vertices of polyhedra and optimal values of linear programming problems.

Theorem 2. *For any* LP *Γ, if $\mathrm{Poly}(\Gamma)$ is bounded, then the optimal value of Γ is reached at some vertex of $\mathrm{Poly}(\Gamma)$.*

Proof. See Theorem 2.3, Theorem 2.4 and Exercise 2.21 in [Sch10].

2.3 Distance Functions and Pseudometrics

In this subsection we introduce distance functions and pseudometrics. Below we fix a set $\mathcal{U}$.

Definition 6 (Distance Functions, Pseudometrics). *A function $d : \mathcal{U} \times \mathcal{U} \to [0,1]$ is a* distance function *over $\mathcal{U}$ iff $d(u,u) = 0$ for all $u \in \mathcal{U}$. A distance function d is further a* pseudometric *over $\mathcal{U}$ iff for all $u, v, w \in \mathcal{U}$, $d(u,v) = d(v,u)$ and $d(u,w) \leq d(u,v) + d(v,w)$. We denote the set of distance functions (*resp. *pseudometrics) over $\mathcal{U}$ by $\mathcal{M}_{\mathrm{d}}(\mathcal{U})$ (*resp. *$\mathcal{M}_{\mathrm{p}}(\mathcal{U})$).*

In the following we use 'κ' to indicate either 'd' or 'p'. In this way we can use "$\mathcal{M}_\kappa(\mathcal{U})$" to make arguments shared by both $\mathcal{M}_{\mathrm{d}}(\mathcal{U})$ and $\mathcal{M}_{\mathrm{p}}(\mathcal{U})$.

Definition 7 (The Partial Order). *The binary relation $\preceq_\kappa$ over $\mathcal{M}_\kappa(\mathcal{U})$ is defined as follows: given $d_1, d_2 \in \mathcal{M}_\kappa(\mathcal{U})$, $d_1 \preceq_\kappa d_2$ iff $d_1(u,v) \geq d_2(u,v)$ for all $u, v \in \mathcal{U}$.*

Clearly, $\preceq_\kappa$ is a partial order over $\mathcal{M}_\kappa(\mathcal{U})$.

Theorem 3. *$(\mathcal{M}_\kappa(\mathcal{U}), \preceq_\kappa)$ is a complete lattice.*

Proof. The bottom element $\bot_\kappa$ is determined by: $\bot_\kappa(u,u) = 0$ and $\bot_\kappa(u,v) = 1$ if $u \neq v$; for all $u, v \in \mathcal{U}$. The top element $\top_\kappa$ is defined by: $\top_\kappa(u,v) = 0$ for all $u, v \in \mathcal{U}$. Given $\mathcal{M} \subseteq \mathcal{M}_\kappa(\mathcal{U})$, the greatest lower bound $\bigsqcap \mathcal{M}$ is given by:

$$\left(\bigsqcap \mathcal{M}\right)(u,v) := \sup\{d(u,v) \mid d \in \mathcal{M}\} \text{ for arbitrary } u, v \in \mathcal{U};$$

And the least upper bound $\bigsqcup \mathcal{M}$ is given by: $\bigsqcup \mathcal{M} = \bigsqcap\{d \in \mathcal{M}_\kappa(\mathcal{U}) \mid \forall d' \in \mathcal{M}. d' \preceq_\kappa d\}$.

3 Distance Functions and Pseudometrics on Probabilistic Automata

In this section we define distance functions and pseudometrics on finite PA. Our pseudometric extends the one on Markov Chains [Pan09,vBSW07], which is defined as a maximum fixed point similar to probabilistic bisimulation [LS91] and shown to be equivalent to the non-future-discounting pseudometric derived from a real-valued logic [Pan09,vBSW07]. Below we fix a finite PA $\mathcal{T} = (S, Act, \Omega)$. We use κ to indicate either 'd' or 'p'.

Definition 8. *Let $d \in \mathcal{M}_\kappa(S)$. Then the element $\Delta(d) \in \mathcal{M}_\kappa(\mathcal{D}(S))$ is given by:*

$$\Delta(d)(\mu,\nu) := \mathrm{OpV}(\Delta_d^{\mu,\nu}), \text{ for all } \mu, \nu \in \mathcal{D}(S)$$

where the LP $\Delta_d^{\mu,\nu}$ is depicted in Tab. 1.

Intuitively, Definition 8 lifts an element of $\mathcal{M}_\kappa(S)$ to an element of $\mathcal{M}_\kappa(\mathcal{D}(S))$. This is however not the original lifting definition. The original one which is derived from the Kantorovich metric [Kan42] is captured by the following definition.

Definition 9. *Given a pseudometric $d \in \mathcal{M}_{\mathrm{p}}(S)$, the pseudometric $\Theta(d) \in \mathcal{M}_{\mathrm{p}}(\mathcal{D}(S))$ is given by: $\Theta(d)(\mu,\nu) := \mathrm{OpV}(\Theta_d^{\mu,\nu})$ for all $\mu, \nu \in \mathcal{D}(S)$, where $\Theta_d^{\mu,\nu}$ is depicted in Tab. 1.*

Table 1. Two Lifting Definitions from $\mathcal{M}_\kappa(S)$ to $\mathcal{M}_\kappa(\mathcal{D}(S))$

$\Theta_d^{\mu,\nu}$	$\Delta_d^{\mu,\nu}$
maximize $\sum_{s\in S}(\mu(s)-\nu(s))\cdot x_s$	minimize $\sum_{s,t\in S} d(s,t)\cdot y_{s,t}$
subject to $\bullet\forall s\in S: 0\le x_s\le 1$	subject to $\bullet\forall s\in S: \sum_{t\in S} y_{s,t}=\mu(s)$
$\bullet\forall s,t\in S: x_s - x_t \le d(s,t)$	$\bullet\forall t\in S: \sum_{s\in S} y_{s,t}=\nu(t)$
	$\bullet\forall s,t\in S: y_{s,t}\ge 0$

By applying the Kantorovich-Rubinstein Duality Theorem [KR58] (cf. [vBSW07]) or the Duality Theorem of linear programming (cf. [vBW01a]), one can show that the two definitions meet on the pseudometrics over S.

Theorem 4. *For any $d\in\mathcal{M}_{\mathrm{p}}(S)$, $\Delta(d)=\Theta(d)$.*

The following two lemmas deal with some basic properties related to Definition 8.

Lemma 1 (Monotonicity). *For any $d_1,d_2\in\mathcal{M}_\kappa(S)$, if $d_1\preceq_\kappa d_2$ then $\Delta(d_1)\preceq_\kappa \Delta(d_2)$.*

Proof. Fix arbitrary $\mu,\nu\in\mathcal{D}(S)$. Denote $P:=\mathrm{Poly}(\Delta_{d_1}^{\mu,\nu})\left(=\mathrm{Poly}(\Delta_{d_2}^{\mu,\nu})\right)$. By $d_1\preceq_\kappa d_2$, we have $\sum_{s,t\in S} d_1(s,t)\cdot y_{s,t}\ge\sum_{s,t\in S} d_2(s,t)\cdot y_{s,t}$ for all $\{y_{s,t}\}_{s,t\in S}\in P$. It follows that $\Delta(d_1)(\mu,\nu)\ge\Delta(d_2)(\mu,\nu)$. Then the result follows.

Lemma 2 (Continuity). *Let $d\in\mathcal{M}_\kappa(S)$ and $\{d_i\}_{i\in\mathbb{N}}$ for which each $d_i\in\mathcal{M}_\kappa(S)$. If $\lim_{i\to\infty} d_i(s,t)=d(s,t)$ for all $s,t\in S$, then $\lim_{i\to\infty}\Delta(d_i)(\mu,\nu)=\Delta(d)(\mu,\nu)$ for all $\mu,\nu\in\mathcal{D}(S)$.*

Proof. Fix arbitrary $\mu,\nu\in\mathcal{D}(S)$. Denote $P:=\mathrm{Poly}(\Delta_{\mathfrak{d}}^{\mu,\nu})$ where the choice of $\mathfrak{d}\in\mathcal{M}_\kappa(S)$ is irrelevant here. By Theorem 2, for all $\mathfrak{d}\in\mathcal{M}_\kappa(S)$,

$$\Delta(\mathfrak{d})(\mu,\nu)=\min\{\sum_{s,t\in S}\mathfrak{d}(s,t)\cdot y_{s,t}\mid\{y_{s,t}\}_{s,t\in S}\text{ is a vertex of }P\}$$

By Theorem 1, the number of vertices of a polyhedron is finite. Then the equation above tells us that $\Delta(\mathfrak{d})(\mu,\nu)$ is continuous on $\mathfrak{d}$. Thus we have $\lim_{i\to\infty}\Delta(d_i)(\mu,\nu)=\Delta(d)(\mu,\nu)$.

Then we define a monotone function $\mathcal{F}_\kappa$ on $\mathcal{M}_\kappa(S)$ as follows.

Definition 10. *The function $\mathcal{F}_\kappa:\mathcal{M}_\kappa(S)\to\mathcal{M}_\kappa(S)$ is given by: for any $d\in\mathcal{M}_\kappa(S)$,*

$$\mathcal{F}_\kappa(d)(s,t):=\max_{a\in Act}\left\{\max\left(\sup_{s\xrightarrow{a}\mu}\inf_{t\xrightarrow{a}\nu}\Delta(d)(\mu,\nu),\sup_{t\xrightarrow{a}\nu}\inf_{s\xrightarrow{a}\mu}\Delta(d)(\mu,\nu)\right)\right\}$$

for arbitrary $s,t\in S$, where $\inf\emptyset:=1$ and $\sup\emptyset:=0$.

One can prove by definition that $\mathcal{F}_\kappa$ is indeed a function $\mathcal{M}_\kappa(S)\to\mathcal{M}_\kappa(S)$ (especially when $\kappa=\mathrm{p}$). Furthermore, it can be proved from Definition 10 and Lemma 1 that $\mathcal{F}_\kappa$ is indeed a monotone function.

Lemma 3. *$\mathcal{F}_\kappa$ is monotone on $\mathcal{M}_\kappa(S)$, i.e., $d_1\preceq_\kappa d_2$ implies $\mathcal{F}_\kappa(d_1)\preceq_\kappa\mathcal{F}_\kappa(d_2)$.*

Remark 2. By definition, $\mathrm{Act}(s) \neq \mathrm{Act}(t)$ implies $\mathcal{F}_\kappa(\mathfrak{d})(s,t) = 1$ and $\mathrm{Act}(s) = \mathrm{Act}(t) = \emptyset$ implies $\mathcal{F}_\kappa(\mathfrak{d})(s,t) = 0$, regardless of the choice of $\mathfrak{d}$.

Since $\mathcal{F}_\kappa$ is monotone, it has a greatest fixed point. This is formulated as follows.

Definition 11. *Define* $\mathbf{d}_\kappa \in \mathcal{M}_\kappa(S)$ *to be the greatest fixed point of* $\mathcal{F}_\kappa$*. By Tarski Fixed-Point Theorem,* $\mathbf{d}_\kappa = \bigsqcup\{d \in \mathcal{M}_\kappa(S) \mid d \preceq_\kappa \mathcal{F}_\kappa(d)\}$.

The pseudometric $\boldsymbol{d}_{\mathrm{p}}$ is closely related with strong bisimulation [SL95] on probabilistic automata: s and t are bisimilar iff $\boldsymbol{d}_{\mathrm{p}}(s,t) = 0$. Here we skip this due to lack of space. One may see [Pan09,vBSW07] for more information. Below we define approximants $\{\boldsymbol{d}^i_\kappa\}_{i\in\mathbb{N}_0}$ of $\boldsymbol{d}_\kappa$.

Definition 12. *The family* $\{\mathbf{d}^i_\kappa\}_{i\in\mathbb{N}_0}$ *of approximants of* $\mathbf{d}_\kappa$ *is inductively defined as follows:* $\mathbf{d}^0_\kappa := \top_\kappa$ *(i.e.,* $\mathbf{d}^0_\kappa(s,t) = 0$ *for all* $s,t \in S$*);* $\mathbf{d}^{i+1}_\kappa = \mathcal{F}_\kappa(\mathbf{d}^i_\kappa)$.

Since $\mathcal{F}_\kappa$ is a monotone function, the sequence $\{\boldsymbol{d}^i_\kappa\}_{i\in\mathbb{N}_0}$ is decreasing w.r.t $\preceq_\kappa$. The following theorem shows that $\boldsymbol{d}_\kappa$ is the limitation of the sequence.

Theorem 5. *For any* $s,t \in S$, $\boldsymbol{d}_\kappa(s,t) = \lim_{i\to\infty} \boldsymbol{d}^i_\kappa(s,t)$.

Proof. Let $\boldsymbol{d}^\infty_\kappa \in \mathcal{M}_\kappa(S)$ be given by $\boldsymbol{d}^\infty_\kappa(s,t) := \lim_{i\to\infty} \boldsymbol{d}^i_\kappa(s,t)$. We prove that $\boldsymbol{d}^\infty_\kappa = \boldsymbol{d}_\kappa$.

$\boldsymbol{d}_\kappa \preceq_\kappa \boldsymbol{d}^\infty_\kappa$: By $\boldsymbol{d}_\kappa \preceq_\kappa \boldsymbol{d}^0_\kappa$ and the monotonicity of $\mathcal{F}$, we can prove by induction on i that $\boldsymbol{d}_\kappa \preceq_\kappa \boldsymbol{d}^i_\kappa$ for all $i \in \mathbb{N}_0$. Thus $\boldsymbol{d}_\kappa \preceq_\kappa \boldsymbol{d}^\infty_\kappa$.

$\boldsymbol{d}^\infty_\kappa \preceq_\kappa \boldsymbol{d}_\kappa$: We prove that $\boldsymbol{d}^\infty_\kappa \preceq_\kappa \mathcal{F}_\kappa(\boldsymbol{d}^\infty_\kappa)$. Fix arbitrary $(s,t) \in S \times S$. Consider any $s \xrightarrow{a} \mu$. By Definition 12, for any $i \in \mathbb{N}$, there exists $t \xrightarrow{a} \nu_i$ such that $\Delta(\boldsymbol{d}^i_\kappa)(\mu,\nu_i) \leq \boldsymbol{d}^{i+1}_\kappa(s,t) \leq \boldsymbol{d}^\infty_\kappa(s,t)$. Since $\mathcal{T}$ is finite, there exists $t \xrightarrow{a} \nu$ such that $\Delta(\boldsymbol{d}^i_\kappa)(\mu,\nu) \leq \boldsymbol{d}^{i+1}_\kappa(s,t) \leq \boldsymbol{d}^\infty_\kappa(s,t)$ for infinitely many $i \in \mathbb{N}$. Then since $\{\boldsymbol{d}^i_\kappa\}_{i\in\mathbb{N}_0}$ is decreasing w.r.t $\preceq_\kappa$ and by Lemma 1, there exists $i \in \mathbb{N}$ such that for all $j \geq i$, $\Delta(\boldsymbol{d}^j_\kappa)(\mu,\nu) \leq \boldsymbol{d}^\infty_\kappa(s,t)$. Thus $\Delta(\boldsymbol{d}^\infty_\kappa)(\mu,\nu) \leq \boldsymbol{d}^\infty_\kappa(s,t)$ by Lemma 2. Similar arguments can be made for all $t \xrightarrow{a} \nu$. Thus $\boldsymbol{d}^\infty_\kappa \preceq_\kappa \mathcal{F}_\kappa(\boldsymbol{d}^\infty_\kappa)$.

Following Theorem 5 and the fact that $\boldsymbol{d}^0_{\mathrm{d}} = \boldsymbol{d}^0_{\mathrm{p}}$, we have the following corollary:

Corollary 1. $\boldsymbol{d}_{\mathrm{p}} = \boldsymbol{d}_{\mathrm{d}} = \bigsqcup\{d \in \mathcal{M}_{\mathrm{d}}(S) \mid d \preceq_{\mathrm{d}} \mathcal{F}_{\mathrm{d}}(d)\}$

This corollary allows us to reason properties of $\boldsymbol{d}_{\mathrm{p}}$ on $\mathcal{M}_{\mathrm{d}}(S)$.

4 NP- and coNP-ness

In this section we study the complexity of the following problem:

- **Input:** a finite PA (S, Act, Ω), $s_{\mathrm{in}}, t_{\mathrm{in}} \in S$ and a number $\epsilon \in \mathbb{Q}_{\geq 0}$ represented in binary
- **Output:** whether $\boldsymbol{d}_{\mathrm{p}}(s_{\mathrm{in}}, t_{\mathrm{in}}) \leq \epsilon$ or not

More precisely, we consider the language

$$\mathcal{L} := \{\langle\langle S, Act, \Omega\rangle, \langle s_{\mathrm{in}}, t_{\mathrm{in}}\rangle, \epsilon\rangle \mid \boldsymbol{d}_{\mathrm{p}}(s_{\mathrm{in}}, t_{\mathrm{in}}) \leq \epsilon\}$$

We prove that $\mathcal{L} \in \mathsf{NP} \cap \mathsf{coNP}$. Our proof method is divided into three steps: First we establish a characterization of the greatest fixed point $\boldsymbol{d}_{\mathrm{p}}$ (or equivalently $\boldsymbol{d}_{\mathrm{d}}$ since $\boldsymbol{d}_{\mathrm{p}} = \boldsymbol{d}_{\mathrm{d}}$); Then based on such characterization, we show that whether a given $d \in \mathcal{M}_{\mathrm{p}}(S)$ equals $\boldsymbol{d}_{\mathrm{p}}$ is polynomial-time decidable; Finally, we complete the proof by showing how we can guess a pseudometric $d \in \mathcal{M}_{\mathrm{p}}(S)$ which is also a fixed point of $\mathcal{F}_{\mathrm{p}}$.

Below we fix a finite PA (S, Act, Ω). First we present the characterization of the greatest fixed point d_{p}. To this end we introduce the notion of "self-fulfilling" sets, as follows:

Definition 13. *Let $d \in \mathcal{M}_{\mathrm{p}}(S)$ with $d = \mathcal{F}_{\mathrm{p}}(d)$. A subset $X \subseteq S \times S$ is* self-fulfilling *w.r.t d iff for any $(s,t) \in X$, the following three conditions hold:*

1. *$d(s,t) > 0$ (which implies that $s \neq t$) and $\mathrm{Act}(s) = \mathrm{Act}(t)$;*
2. *for any $s \xrightarrow{a} \mu$ such that $d(s,t) = \inf\{\Delta(d)(\mu,\nu) \mid t \xrightarrow{a} \nu\}$, there is $t \xrightarrow{a} \nu_0$ and $y = \{y_{s,t}\}_{s,t\in S} \in \mathrm{OpS}(\Delta_d^{\mu,\nu_0})$ such that $d(s,t) = \Delta(d)(\mu,\nu_0)$ and $\lfloor y \rfloor \subseteq X$.*
3. *for any $t \xrightarrow{a} \nu$ such that $d(s,t) = \inf\{\Delta(d)(\mu,\nu) \mid s \xrightarrow{a} \mu\}$, there is $s \xrightarrow{a} \mu_0$ and $y = \{y_{s,t}\}_{s,t\in S} \in \mathrm{OpS}(\Delta_d^{\mu_0,\nu})$ such that $d(s,t) = \Delta(d)(\mu_0,\nu)$ and $\lfloor y \rfloor \subseteq X$.*

where $\lfloor y \rfloor := \{(s,t) \in S \times S \mid y_{s,t} > 0\}$.

Intuitively, a self-fulfilling set X w.r.t d is a set such that all values $d(s,t)$ of d in X can be reached on X itself. Below we show that nonempty self-fulfilling sets characterize exactly the greatest fixed point $\boldsymbol{d}_{\mathrm{p}}$ of the function $\mathcal{F}_{\mathrm{p}}$.

Theorem 6. *Let $d \in \mathcal{M}_{\mathrm{p}}(S)$ such that $d = \mathcal{F}_{\mathrm{p}}(d)$. If $d \neq \boldsymbol{d}_{\mathrm{p}}$, then there exists a nonempty self-fulfilling set $X \subseteq S \times S$ with respect to d.*

Proof. Suppose $d \neq \boldsymbol{d}_{\mathrm{p}}$, we construct a nonempty self-fulfilling set X as described below. Denote $\delta(s,t) = d(s,t) - \boldsymbol{d}_{\mathrm{p}}(s,t)$. Then $\delta(s,t) \geq 0$ for all $s,t \in S$, and there is $(s,t) \in S \times S$ such that $\delta(s,t) > 0$ due to $d \neq \boldsymbol{d}_{\mathrm{p}}$. Define X to be the following set:

$$X := \{(s,t) \in S \times S \mid \delta(s,t) = \max\{\delta(s',t') \mid (s',t') \in S \times S\}\}$$

We prove that X is a nonempty self-fulfilling set. The non-emptiness of X is obvious. We further prove that any $(s,t) \in X$ satisfies the three conditions specified in Definition 13. Fix arbitrary $(s,t) \in X$. The analysis is as follows:

1. It is clear that $d(s,t) > 0$ since $\delta(s,t) > 0$. We prove that $\mathrm{Act}(s) = \mathrm{Act}(t)$. Suppose $\mathrm{Act}(s) \neq \mathrm{Act}(t)$. Then by Remark 2, $d(s,t) = \boldsymbol{d}_{\mathrm{p}}(s,t) = 1$ which implies $\delta(s,t) = 0$. Contradiction. So (s,t) satisfies the first condition in Definition 13.
2. Suppose that $s \xrightarrow{a} \mu$ satisfies $d(s,t) = \inf\{\Delta(d)(\mu,\nu) \mid t \xrightarrow{a} \nu\}$ and $t \xrightarrow{a} \nu_0$ be arbitrarily chosen satisfying $\Delta(\boldsymbol{d}_{\mathrm{p}})(\mu,\nu_0) = \inf\{\Delta(\boldsymbol{d}_{\mathrm{p}})(\mu,\nu) \mid t \xrightarrow{a} \nu\}$. Choose an arbitrary $y = \{y_{s,t}\}_{s,t\in S} \in \mathrm{OpS}(\Delta_{\boldsymbol{d}_{\mathrm{p}}}^{\mu,\nu_0})$. We prove that $y \in \mathrm{OpS}(\Delta_d^{\mu,\nu_0})$ and $\lfloor y \rfloor \subseteq X$ (cf. Definition 13). By the definition of X, we have $\delta(s',t') \leq \delta(s,t)$ for all $(s',t') \in S \times S$. Thus for any $\{y^*_{s,t}\}_{s,t\in S} \in \mathrm{Poly}(\Delta_d^{\mu,\nu_0})$, we have

$$\sum_{s',t'\in S} \boldsymbol{d}_{\mathrm{p}}(s',t') \cdot y^*_{s',t'} \geq \sum_{s',t'\in S} (d(s',t') - \delta(s,t)) \cdot y^*_{s',t'} \tag{1}$$

Since $\sum_{s',t' \in S} y^*_{s',t'} = 1$, we can further simplify Inequality (1) as follows:

$$\sum_{s',t' \in S} \boldsymbol{d}_{\mathrm{p}}(s',t') \cdot y^*_{s',t'} \geq \sum_{s',t' \in S} d(s',t') \cdot y^*_{s',t'} - \delta(s,t) \tag{2}$$

Note that $\mathrm{Poly}(\Delta_d^{\mu,\nu_0}) = \mathrm{Poly}(\Delta_{\boldsymbol{d}_{\mathrm{p}}}^{\mu,\nu_0})$. So by taking the infimum at the both sides of Inequality 2, we obtain that $\Delta(\boldsymbol{d}_{\mathrm{p}})(\mu,\nu_0) \geq \Delta(d)(\mu,\nu_0) - \delta(s,t)$. Further from Definition 10, we obtain $\boldsymbol{d}_{\mathrm{p}}(s,t) \geq \Delta(\boldsymbol{d}_{\mathrm{p}})(\mu,\nu_0)$. Thus, we have:

$$\boldsymbol{d}_{\mathrm{p}}(s,t) \geq \Delta(\boldsymbol{d}_{\mathrm{p}})(\mu,\nu_0) \geq \Delta(d)(\mu,\nu_0) - \delta(s,t) \geq d(s,t) - \delta(s,t) = \boldsymbol{d}_{\mathrm{p}}(s,t)$$

This means that $\boldsymbol{d}_{\mathrm{p}}(s,t) = \Delta(\boldsymbol{d}_{\mathrm{p}})(\mu,\nu_0)$ and $d(s,t) = \Delta(d)(\mu,\nu_0)$. Then we can form another inequality series as follows:

$$\begin{aligned}
&\textstyle\sum_{s',t' \in S} d(s',t') \cdot y_{s',t'} \\
&\geq d(s,t) && (\text{by } d(s,t) = \Delta(d)(\mu,\nu_0)) \\
&= \boldsymbol{d}_{\mathrm{p}}(s,t) + \delta(s,t) \\
&= \textstyle\sum_{s',t' \in S} \boldsymbol{d}_{\mathrm{p}}(s',t') \cdot y_{s',t'} + \delta(s,t) && (\text{by } \boldsymbol{d}_{\mathrm{p}}(s,t) = \Delta(\boldsymbol{d}_{\mathrm{p}})(\mu,\nu_0)) \\
&= \textstyle\sum_{s',t' \in S} (\boldsymbol{d}_{\mathrm{p}}(s',t') + \delta(s,t)) \cdot y_{s',t'} \\
&\geq \textstyle\sum_{s',t' \in S} (\boldsymbol{d}_{\mathrm{p}}(s',t') + \delta(s',t')) \cdot y_{s',t'} \\
&= \textstyle\sum_{s',t' \in S} d(s',t') \cdot y_{s',t'}
\end{aligned}$$

Thus it must be the case that $y \in \mathrm{OpS}(\Delta_d^{\mu,\nu_0})$ and $\delta(s',t') = \delta(s,t)$ whenever $y_{s',t'} > 0$. Then we have $\lfloor y \rfloor \subseteq X$. So (s,t) satisfies the second condition in Definition 13.

3. Symmetrically we can prove that (s,t) satisfies the third condition in Definition 13.

Hence in conclusion, X is a self-fulfilling set.

Theorem 7. *Let $d \in \mathcal{M}_{\mathrm{p}}(S)$ such that $d = \mathcal{F}_{\mathrm{p}}(d)$. If there exists a nonempty self-fulfilling set $X \subseteq S \times S$ with respect to d, then $d \neq \boldsymbol{d}_{\mathrm{p}}$.*

Proof. Suppose $X \subseteq S \times S$ is a nonempty self-fulfilling set w.r.t d. We construct a distance function $d' \neq d$ such that $d' \preceq_{\mathrm{d}} \mathcal{F}_{\mathrm{d}}(d')$ and $d \preceq_{\mathrm{d}} d'$. For all $(s \xrightarrow{a} \mu, t)$ and all $(s, t \xrightarrow{a} \nu)$ such that $(s,t) \in X$, we define the following differences: (note that $\mathrm{Act}(s) = \mathrm{Act}(t)$)

- $\delta[s \xrightarrow{a} \mu, t] := d(s,t) - \inf\{\Delta(d)(\mu,\nu') \mid t \xrightarrow{a} \nu'\}$;
- $\delta[s, t \xrightarrow{a} \nu] := d(s,t) - \inf\{\Delta(d)(\mu',\nu) \mid s \xrightarrow{a} \mu'\}$.

All the differences defined above are non-negative since $d = \mathcal{F}_{\mathrm{p}}(d)$. Further we define the following two differences: (where $\min \emptyset := 0$)

- $\delta_1 := \min\{\delta[s \xrightarrow{a} \mu, t] \mid (s,t) \in X, s \xrightarrow{a} \mu \text{ and } \delta[s \xrightarrow{a} \mu, t] > 0\}$;
- $\delta_2 := \min\{\delta[s, t \xrightarrow{a} \nu] \mid (s,t) \in X, t \xrightarrow{a} \nu \text{ and } \delta[s, t \xrightarrow{a} \nu] > 0\}$.

Finally we define the difference value δ as follows:

$$\delta := \begin{cases}
\min\{\delta_1, \delta_2, \min\{d(s,t) \mid (s,t) \in X\}\} & \text{if } \delta_1 \neq 0 \text{ and } \delta_2 \neq 0 \\
\min\{\delta_2, \min\{d(s,t) \mid (s,t) \in X\}\} & \text{if } \delta_1 = 0 \text{ and } \delta_2 \neq 0 \\
\min\{\delta_1, \min\{d(s,t) \mid (s,t) \in X\}\} & \text{if } \delta_1 \neq 0 \text{ and } \delta_2 = 0 \\
\min\{d(s,t) \mid (s,t) \in X\} & \text{if } \delta_1 = 0 \text{ and } \delta_2 = 0
\end{cases}$$

Note that $\delta > 0$. Then we construct $d' \in \mathcal{M}_{\mathrm{d}}(S)$ by:

$$d'(s,t) := \begin{cases} d(s,t) - \frac{1}{2}\delta & \text{if } (s,t) \in X \\ d(s,t) & \text{if } (s,t) \notin X \end{cases}$$

It is clear that $d' \neq d$ since X is non-empty. We prove that $d' \preceq_{\mathrm{d}} \mathcal{F}_{\mathrm{d}}(d')$. Fix an arbitrary $(s,t) \in S \times S$. Suppose $(s,t) \notin X$. Then from $d \preceq_{\mathrm{d}} d'$ we have $\mathcal{F}_{\mathrm{d}}(d) \preceq_{\mathrm{d}} \mathcal{F}_{\mathrm{d}}(d')$. And then we have $d'(s,t) = d(s,t) = \mathcal{F}_{\mathrm{p}}(d)(s,t) = \mathcal{F}_{\mathrm{d}}(d)(s,t) \geq \mathcal{F}_{\mathrm{d}}(d')(s,t)$. Thus $d'(s,t) \geq \mathcal{F}_{\mathrm{d}}(d')(s,t)$. Suppose now that $(s,t) \in X$. For any $s \xrightarrow{a} \mu$, we clarify two cases below:

Case 1: $\delta[s \xrightarrow{a} \mu, t] > 0$. Then $\delta_1 > 0$. By definition, we have:

$$d'(s,t) \geq d(s,t) - \frac{1}{2}\delta > d(s,t) - \delta[s \xrightarrow{a} \mu, t] = \inf\{\Delta(d)(\mu,\nu') \mid t \xrightarrow{a} \nu'\}$$

From $d \preceq_{\mathrm{d}} d'$, we have $\inf\{\Delta(d)(\mu,\nu') \mid t \xrightarrow{a} \nu'\} \geq \inf\{\Delta(d')(\mu,\nu') \mid t \xrightarrow{a} \nu'\}$. Thus $d'(s,t) \geq \inf\{\Delta(d')(\mu,\nu') \mid t \xrightarrow{a} \nu'\}$.

Case 2: $\delta[s \xrightarrow{a} \mu, t] = 0$. Then since X is self-fulfilling there is $t \xrightarrow{a} \nu_0$ and $y = \{y_{s',t'}\}_{s',t' \in S} \in \mathrm{OpS}(\Delta_d^{\mu,\nu_0})$ such that $d(s,t) = \Delta(d)(\mu,\nu_0)$ and $\lfloor y \rfloor \subseteq X$. From $\lfloor y \rfloor \subseteq X$ we obtain

$$\sum_{s',t' \in S} d'(s',t') \cdot y_{s',t'} = \sum_{s',t' \in S} d(s',t') \cdot y_{s',t'} - \frac{1}{2}\delta = \Delta(d)(\mu,\nu_0) - \frac{1}{2}\delta = d'(s,t)$$

Then we have: $\inf\{\Delta(d')(\mu,\nu') \mid t \xrightarrow{a} \nu'\} \leq \Delta(d')(\mu,\nu_0) \leq \sum_{s',t' \in S} d'(s',t') \cdot y_{s',t'} = d'(s,t)$. Thus $d'(s,t) \geq \inf\{\Delta(d')(\mu,\nu') \mid t \xrightarrow{a} \nu'\}$ for all $s \xrightarrow{a} \mu$. Similarly we can prove that $d'(s,t) \geq \inf\{\Delta(d')(\mu',\nu) \mid s \xrightarrow{a} \mu'\}$ for all $t \xrightarrow{a} \nu$. Thus $d'(s,t) \geq \mathcal{F}_{\mathrm{d}}(d')(s,t)$ for all $(s,t) \in S \times S$. Hence $d' \preceq_{\mathrm{d}} \mathcal{F}_{\mathrm{d}}(d')$. By $d \preceq_{\mathrm{d}} d'$ we have $d \neq \bigsqcup\{\mathfrak{d} \in \mathcal{M}_{\mathrm{d}}(S) | \mathfrak{d} \preceq_{\mathrm{d}} \mathcal{F}_{\mathrm{d}}(\mathfrak{d})\}$. Then by Corollary 1, we obtain that $d \neq \boldsymbol{d}_{\mathrm{p}}$.

Thus for any $d \in \mathcal{M}_{\mathrm{p}}(S)$ satisfying $d = \mathcal{F}_{\mathrm{p}}(d)$, $d \neq \boldsymbol{d}_{\mathrm{p}}$ iff there exists a nonempty self-fulfiling set w.r.t d. This characterization means that to check whether $d \neq \boldsymbol{d}_{\mathrm{p}}$ or not, we can equivalently check whether there exists a nonempty self-fulfilling set or not. The intuition here is that for any self-fulfilling sets X, Y, $X \cup Y$ is still a self-fulfilling set; thus there exists a largest self-fulfilling set. This gives rise to a refinement algorithm that computes the largest self-fulfilling set.

Theorem 8. *Denote* $\mathrm{FP} := \{d \in \mathcal{M}_{\mathrm{p}}(S) \mid d = \mathcal{F}_{\mathrm{p}}(d)\}$ *to be the set of fixed points of* $\mathcal{F}_{\mathrm{p}}$. *The problem whether a given* $d \in \mathrm{FP}$ *equals* $\boldsymbol{d}_{\mathrm{p}}$ *is decidable in polynomial time.*

Proof. From Theorem 6 and Theorem 7, we can solve the problem by checking whether there exists a nonempty self-fulfilling set w.r.t the given $d \in \mathrm{FP}$. Note that for any self-fulfilling sets X, Y w.r.t d, $X \cup Y$ is still self-fulfilling w.r.t d. So there exists a largest self-fulfilling set w.r.t d, which is denoted as Z. Then there exists a nonempty self-fulfilling set w.r.t d iff Z is nonempty. Below we develop a refinement algorithm to compute Z.

First we define a refinement function $ref : \mathcal{E} \to \mathcal{E}$, where the set $\mathcal{E}$ is given as follows:

$$\mathcal{E} := \{X \subseteq S \times S \mid \mathrm{Act}(s) = \mathrm{Act}(t) \text{ and } d(s,t) > 0 \text{ for all } (s,t) \in X\}$$

Note that $\mathcal{E}$ is nonempty since $\emptyset \in \mathcal{E}$. Given $X \in \mathcal{E}$, we define $\delta_X := \min\{d(s,t) \mid (s,t) \in X\}$ (where $\min \emptyset = 0$) and the distance function $d_X \in \mathcal{M}_{\mathrm{d}}(S)$ as follows:

$$d_X(s,t) = \begin{cases} d(s,t) - \delta_X & \text{if } (s,t) \in X \\ d(s,t) & \text{if } (s,t) \notin X \end{cases}$$

Then the set $ref(X) \in \mathcal{E}$ is defined as follows: $(s,t) \in ref(X)$ iff $(s,t) \in X$ and further (s,t) satisfies the following two conditions:

1. for all $s \xrightarrow{a} \mu$, if $d(s,t) = \inf\{\Delta(d)(\mu,\nu) \mid t \xrightarrow{a} \nu\}$ then: $d_X(s,t) \geq \inf\{\Delta(d_X)(\mu,\nu) \mid t \xrightarrow{a} \nu\}$
2. for all $t \xrightarrow{a} \nu$, if $d(s,t) = \inf\{\Delta(d)(\mu,\nu) \mid s \xrightarrow{a} \mu\}$ then: $d_X(s,t) \geq \inf\{\Delta(d_X)(\mu,\nu) \mid s \xrightarrow{a} \mu\}$

Note that $ref(X) \subseteq X$ for all $X \in \mathcal{E}$. Now we construct a sequence $\{Z_i\}_{i \in \mathbb{N}_0}$ as follows:

$$Z_0 = \{(s,t) \in S \times S \mid \mathrm{Act}(s) = \mathrm{Act}(t) \text{ and } d(s,t) > 0\};\ Z_{i+1} = ref(Z_i)$$

By $Z_{i+1} \subseteq Z_i$, there exists $n \leq |Z_0|$ such that $Z_{n+1} = ref(Z_n) = Z_n$. We show that $Z_n = Z$.

"$Z \subseteq Z_n$": We prove by induction that $Z \subseteq Z_i$ for all $i \in \mathbb{N}_0$. The base step $Z \subseteq Z_0$ is clear from the definition. For inductive step, suppose that $Z \subseteq Z_i$. We show that $Z \subseteq Z_{i+1} (= ref(Z_i))$. Fix arbitrary $(s,t) \in Z$. Consider any $s \xrightarrow{a} \mu$ such that $d(s,t) = \inf\{\Delta(d)(\mu,\nu) \mid t \xrightarrow{a} \nu\}$. Since Z is self-fulfilling, there is $t \xrightarrow{a} \nu_0$ and $y = \{y_{s',t'}\}_{s',t' \in S} \in \mathrm{OpS}(\Delta_d^{\mu,\nu_0})$ such that $d(s,t) = \Delta(d)(\mu,\nu_0)$ and $\lfloor y \rfloor \subseteq Z$. Since $Z \subseteq Z_i$, we have $d_{Z_i}(s,t) = d(s,t) - \delta_{Z_i}$ and $d_{Z_i}(s',t') = d(s',t') - \delta_{Z_i}$ for all $(s',t') \in \lfloor y \rfloor$. Thus we obtain

$$\sum_{s',t' \in S} d_{Z_i}(s',t') \cdot y_{s',t'} = \sum_{s',t' \in S} (d(s',t') - \delta_{Z_i}) \cdot y_{s',t'} = d(s,t) - \delta_{Z_i} = d_{Z_i}(s,t)$$

Hence $d_{Z_i}(s,t) \geq \Delta(d_{Z_i})(\mu,\nu_0) \geq \inf\{\Delta(d_{Z_i})(\mu,\nu) \mid t \xrightarrow{a} \nu\}$. By a similar reasoning we can prove that for all $t \xrightarrow{a} \nu$, if $d(s,t) = \inf\{\Delta(d)(\mu,\nu) \mid s \xrightarrow{a} \mu\}$ then $d_{Z_i}(s,t) \geq \inf\{\Delta(d_{Z_i})(\mu,\nu) \mid s \xrightarrow{a} \mu\}$. So $(s,t) \in Z_{i+1}$. Thus $Z \subseteq Z_{i+1}$.

"$Z_n \subseteq Z$": We prove that Z_n is a self-fulfilling set, i.e., Z_n satisfies the three conditions specified in Definition 13. W.l.o.g we can assume that $Z_n \neq \emptyset$. The first condition in Definition 13 is directly satisfied since $Z_n \subseteq Z_0$. As for the second condition, consider any $(s,t) \in Z_n$ and $s \xrightarrow{a} \mu$ satisfying $d(s,t) = \inf\{\Delta(d)(\mu,\nu) \mid t \xrightarrow{a} \nu\}$. By $Z_n = ref(Z_n)$, $d_{Z_n}(s,t) \geq \inf\{\Delta(d_{Z_n})(\mu,\nu) \mid t \xrightarrow{a} \nu\}$. Choose $t \xrightarrow{a} \nu_0$ such that $\Delta(d_{Z_n})(\mu,\nu_0) = \inf\{\Delta(d_{Z_n})(\mu,\nu) \mid t \xrightarrow{a} \nu\}$ and an arbitrary $y \in \mathrm{OpS}(\Delta_{d_{Z_n}}^{\mu,\nu_0})$. Then since $d_{Z_n}(s,t) = d(s,t) - \delta_{Z_n}$, we have

$$\begin{aligned} d(s,t) &\geq \Delta(d_{Z_n})(\mu,\nu_0) + \delta_{Z_n} \\ &= \textstyle\sum_{s',t' \in S} (d_{Z_n}(s',t') + \delta_{Z_n}) \cdot y_{s',t'} \\ &\geq \textstyle\sum_{s',t' \in S} d(s',t') \cdot y_{s',t'} \\ &\geq \Delta(d)(\mu,\nu_0) \\ &\geq d(s,t) \end{aligned}$$

Thus $d(s,t) = \Delta(d)(\mu,\nu_0)$, $y \in \mathrm{OpS}(\Delta_d^{\mu,\nu_0})$ and $d_{Z_n}(s',t') = d(s',t') - \delta_{Z_n}$ for all $(s',t') \in \lfloor y \rfloor$, which implies that $\lfloor y \rfloor \subseteq Z_n$ since $\delta_{Z_n} > 0$. Then the result follows.

The reasoning for the third condition can be carried out in the same way as for the second condition.

Thus to compute Z, we need only to apply ref to Z_0 at most $|Z_0|$ times. Note that the computation of ref can be carried out in polynomial time since the optimal value of a linear programming problem can be computed in polynomial time. Hence Z is polynomial-time computable. Then it follows directly that whether a given $d \in \mathrm{FP}$ equals $\boldsymbol{d}_{\mathrm{p}}$ is decidable in polynomial time.

By Theorem 8, we can decide if a given element in FP is $\boldsymbol{d}_{\mathrm{p}}$ in polynomial time. However, it does not tell us how to obtain an element in FP. Below we show that we can guess such an element using only polynomial random-bits. This is also the final step to prove that $\mathcal{L} \in \mathsf{NP} \cap \mathsf{coNP}$. (see the beginning of the section for the definition of $\mathcal{L}$)

Theorem 9. $\mathcal{L} \in \mathsf{NP} \cap \mathsf{coNP}$.

Proof. We only show that $\mathcal{L}^{\mathrm{c}} \in \mathsf{NP}$, since proving $\mathcal{L} \in \mathsf{NP}$ is similar. W.l.o.g we assume that $\mathcal{L}^{\mathrm{c}} := \{\langle\langle S, Act, \Omega\rangle, \langle s_{\mathrm{in}}, t_{\mathrm{in}}\rangle, \epsilon\rangle \mid \boldsymbol{d}_{\mathrm{p}}(s_{\mathrm{in}}, t_{\mathrm{in}}) > \epsilon\}$. Let (S, Act, Ω), $(s_{\mathrm{in}}, t_{\mathrm{in}})$ and ϵ be the input. Our strategy to obtain a NP algorithm for $\mathcal{L}^{\mathrm{c}}$ is as follows:

1. We guess a $d \in \mathrm{FP}$ by using Theorem 2 and Theorem 1.
2. We check whether $d = \boldsymbol{d}_{\mathrm{p}}$ by Theorem 8; if $d = \boldsymbol{d}_{\mathrm{p}}$ then we check whether $d(s,t) > \epsilon$, otherwise we fail.

Below we show that how we can guess a $d \in \mathrm{FP}$ using only polynomial bits. The guessing procedure is illustrated step by step as follows.

1. For all $s \xrightarrow{a} \mu$ and $t \in S$ such that $\mathrm{Act}(s) = \mathrm{Act}(t) \neq \emptyset$, we guess a $\nu[s \xrightarrow{a} \mu, t]$ such that $t \xrightarrow{a} \nu[s \xrightarrow{a} \mu, t]$. Then we guess $|S|^2$ constraints (informally "rows") specified in the LP $\Delta_{\mathfrak{d}}^{\mu,\nu[s\xrightarrow{a}\mu,t]}$ (cf. Tab. 1). Note that the parameter $\mathfrak{d}$ is irrelevant here. We denote the guessed collection of constraints (w.r.t $s \xrightarrow{a} \mu$ and t) as $\{h_i^T y \ \mathrm{op}_i \ b^i\}_{i \in I[s\xrightarrow{a}\mu,t]}$, where
   - $y = \{y_{s',t'}\}_{s',t' \in S}$ represents the variable vector;
   - $I[s \xrightarrow{a} \mu, t]$ is the set of indexes of the guessed rows;
   - $h_i^T y \ \mathrm{op}_i \ b^i$ is the constraint at the i-th row, for which $\mathrm{op}_i \in \{\leq, \geq, =\}$ is the comparison operator at the i-th row.

   We check in polynomial time whether for all $s \xrightarrow{a} \mu$ and $t \in S$, the linear equation system $\{h_i^T y = b^i\}_{i \in I[s\xrightarrow{a}\mu,t]}$ has a unique solution (through, e.g., Gaussian Elimination). We fail if the checking result is negative; Otherwise we denote the unique solution to be $y[s \xrightarrow{a} \mu, t]$ (a vector over $S \times S$), and proceed to the next step.
2. For all $t \xrightarrow{a} \nu$ and $s \in S$ such that $\mathrm{Act}(s) = \mathrm{Act}(t) \neq \emptyset$, we perform similar guessings illustrated in Step 1. We guess a $\mu[s, t \xrightarrow{a} \nu]$, and further $|S|^2$ constraints specified in the LP $\Delta_{\mathfrak{d}}^{\mu[s,t\xrightarrow{a}\nu],\nu}$. We denote the guessed constraints as $\{h_i^T y \ \mathrm{op}_i \ b^i\}_{i \in I[s,t\xrightarrow{a}\nu]}$. Then we check whether for all $t \xrightarrow{a} \nu$ and $s \in S$, the linear equation system $\{h_i^T y = b^i\}_{i \in I[s,t\xrightarrow{a}\nu]}$ has a unique solution. We fail if the checking result is negative; Otherwise we denote the unique solution as $y[s, t \xrightarrow{a} \nu]$, and proceed to the next step.

3. We compute a distance function $d \in \mathcal{M}_{\mathrm{d}}(S)$ defined by: $d(s,t) = \mathrm{OpV}(\Gamma_{s,t})$ for all $s,t \in S$, where the LP $\Gamma_{s,t}$ (with variables $\{z_{s',t'}\}_{s',t' \in S}$) is specified by:

   minimize $z_{s,t}$
   subject to:
   (i) $z_{s',s'} = 0$, $z_{s',t'} = z_{t',s'}$ and $z_{r',t'} \le z_{r',s'} + z_{s',t'}$ for all $r',s',t' \in S$
   (ii) $0 \le z_{s',t'} \le 1$ for all $s',t' \in S$
   (iii) $z_{s',t'} \ge \sum_{\mathfrak{s},\mathfrak{t} \in S} (y[s' \xrightarrow{a} \mu, t'])_{\mathfrak{s},\mathfrak{t}} \cdot z_{\mathfrak{s},\mathfrak{t}}$ for all $t' \in S$ and all $s' \xrightarrow{a} \mu$ such that $\mathrm{Act}(s') = \mathrm{Act}(t') \neq \emptyset$
   (iv) $z_{s',t'} \ge \sum_{\mathfrak{s},\mathfrak{t} \in S} (y[s', t' \xrightarrow{a} \nu])_{\mathfrak{s},\mathfrak{t}} \cdot z_{\mathfrak{s},\mathfrak{t}}$ for all $s' \in S$ and all $t' \xrightarrow{a} \nu$ such that $\mathrm{Act}(s') = \mathrm{Act}(t') \neq \emptyset$
   (v) $z_{s',t'} = 0$ for all $s',t' \in S$ such that $\mathrm{Act}(s') = \mathrm{Act}(t') = \emptyset$.
   (vi) $z_{s',t'} = 1$ for all $s',t' \in S$ such that $\mathrm{Act}(s') \neq \mathrm{Act}(t')$.
   If there is $\Gamma_{s,t}$ that has no feasible solution (which can also be decided in polynomial time), we fail; Otherwise we proceed to the next step.
4. We check whether $d \in \mathcal{M}_{\mathrm{p}}(S)$ and $d = \mathcal{F}_{\mathrm{p}}(d)$, which can be done in polynomial time. We fail if the checking is unsuccessful; otherwise we have guessed a $d \in \mathrm{FP}$.

Then (as is previously mentioned), the final step is to check whether $d = \boldsymbol{d}_{\mathrm{p}}$: if $d = \boldsymbol{d}_{\mathrm{p}}$ then we return the comparison result of $d(s,t) > \epsilon$; otherwise we fail. It is clear that if we can guess a $d \in \mathrm{FP}$ and check successfully that $d = \boldsymbol{d}_{\mathrm{p}}$, then the returned result is surely correct. Below we prove that $\boldsymbol{d}_{\mathrm{p}}$ can be guessed through the guessing procedure.

Consider Step 1. For any $s \xrightarrow{a} \mu$ and $t \in S$ such that $\mathrm{Act}(s) = \mathrm{Act}(t) \neq \emptyset$, we choose $\nu[s \xrightarrow{a} \mu, t]$ such that $\Delta(\boldsymbol{d}_{\mathrm{p}})(\mu, \nu[s \xrightarrow{a} \mu, t]) = \inf\{\Delta(\boldsymbol{d}_{\mathrm{p}})(\mu,\nu) \mid t \xrightarrow{a} \nu\}$. By Theorem 2, we can choose $y[s \xrightarrow{a} \mu, t]$ to be a vertex of $\Delta_{\mathfrak{d}}^{\mu,\nu[s \xrightarrow{a} \mu,t]}$ that reaches $\mathrm{OpV}(\Delta_{\mathfrak{d}}^{\mu,\nu[s \xrightarrow{a} \mu,t]})$. Then by Theorem 1, we choose constraints $\{h_i^T y \ \mathrm{op}_i \ b^i\}_{i \in I[s \xrightarrow{a} \mu,t]}$ such that $\{h_i^T\}_{i \in I[s \xrightarrow{a} \mu,t]}$ are exactly the row vectors of the matrix $A_{y[s \xrightarrow{a} \mu,t]}$ (cf. Theorem 1). Here by Remark 1, we can abuse Theorem 1 on constraints like "$h^T y \ge e$" and "$h^T y = e$". Then surely the unique solution of $\{h_i^T y = b^i\}_{i \in I[s \xrightarrow{a} \mu,t]}$ is $y[s \xrightarrow{a} \mu, t]$. Similarly, we choose $y[s,t \xrightarrow{a} \nu]$ for all $s \in S$ and $t \xrightarrow{a} \nu$ such that $\mathrm{Act}(s) = \mathrm{Act}(t) \neq \emptyset$ in Step 2.

Then consider Step 3. We show that the $d \in \mathcal{M}_{\mathrm{d}}(S)$ defined in Step 3 is equal to $\boldsymbol{d}_{\mathrm{p}}$, provided that $y[s' \xrightarrow{a} \mu, t']$ and $y[s', t' \xrightarrow{a} \nu]$ are chosen as above.

1. $\boldsymbol{d}_{\mathrm{p}} \preceq_{\mathrm{d}} d$: By the definition of pseudometrics and Remark 2, the vector $\{z^*_{s',t'}\}_{s',t' \in S}$ is a feasible solution of $\Gamma_{s,t}$ for all $s,t \in S$, where $\{z^*_{s',t'}\}_{s',t' \in S}$ is given by: $z^*_{s',t'} = \boldsymbol{d}_{\mathrm{p}}(s',t')$ for all $s',t' \in S$. Thus immediately we have $\boldsymbol{d}_{\mathrm{p}} \preceq_{\mathrm{d}} d$.
2. $d \preceq_{\mathrm{d}} \boldsymbol{d}_{\mathrm{p}}$: Fix arbitrary $(s,t) \in S \times S$ and let $\{\mathbf{z}_{s',t'}\}_{s',t' \in S}$ be an optimal solution of $\Gamma_{s,t}$. Define $d' \in \mathcal{M}_{\mathrm{d}}(S)$ by: $d'(s',t') = \mathbf{z}_{s',t'}$ for arbitrary $s',t' \in S$. Then for any $t' \in S$ and $s' \xrightarrow{a} \mu$ such that $\mathrm{Act}(s') = \mathrm{Act}(t') \neq \emptyset$,

$$d'(s',t') \ge \sum_{\mathfrak{s},\mathfrak{t} \in S} (y[s' \xrightarrow{a} \mu, t'])_{\mathfrak{s},\mathfrak{t}} \cdot d'(\mathfrak{s},\mathfrak{t}) \ge \Delta(d')(\mu, \nu[s' \xrightarrow{a} \mu, t'])$$

   Hence $d'(s',t') \ge \inf\{\Delta(d')(\mu,\nu) \mid t' \xrightarrow{a} \nu\}$. In a similar way, we can prove that $d'(s',t') \ge \inf\{\Delta(d')(\mu,\nu) \mid s' \xrightarrow{a} \mu\}$ for all $s' \in S$ and $t' \xrightarrow{a} \nu$ such

that $\mathrm{Act}(s') = \mathrm{Act}(t') \neq \emptyset$. Thus $d' \preceq_{\mathrm{d}} \mathcal{F}_{\mathrm{d}}(d')$ and hence $d' \preceq_{\mathrm{d}} \boldsymbol{d}_{\mathrm{p}}$. Then $d(s,t) \geq \boldsymbol{d}_{\mathrm{p}}(s,t)$ since $d(s,t) = d'(s,t)$.

In conclusion, $\boldsymbol{d}_{\mathrm{p}}$ can be obtained on certain random bits in the guessing procedure.

5 Conclusion and Future Work

We have shown that the problem whether the distance between two given states of a finite simple probabilistic automata under a non-future-discounting pseudometric derived from a real-valued logic lies in $\mathsf{NP} \cap \mathsf{coNP}$, which significantly improves previous PSPACE upperbound [vBSW07,CHL09]. We prove this by establishing the original notion of "self-fulfilling" sets, and then exploring the relationship between our pseudometric and self-fulfilling sets. Our future work is to investigate if the problem further lies in PTIME, and whether there is an efficient error-tolerant algorithm for this problem. It is also possible to extend the result of this paper to game metrics [dAMRS07].

References

[ASB95] Adnan Aziz, Vigyan Singhal, and Felice Balarin. It usually works: The temporal logic of stochastic systems. In *CAV*, pages 155–165, 1995.

[BEMC00] Christel Baier, Bettina Engelen, and Mila E. Majster-Cederbaum. Deciding bisimilarity and similarity for probabilistic processes. *J. Comput. Syst. Sci.*, 60(1):187–231, 2000.

[CHL09] Taolue Chen, Tingting Han, and Jian Lu. On metrics for probabilistic systems: Definitions and algorithms. *Computers & Mathematics with Applications*, 57(6):991–999, 2009.

[CS02] Stefano Cattani and Roberto Segala. Decision algorithms for probabilistic bisimulation. In *CONCUR*, pages 371–385, 2002.

[dAMRS07] Luca de Alfaro, Rupak Majumdar, Vishwanath Raman, and Mariëlle Stoelinga. Game relations and metrics. In *LICS*, pages 99–108, 2007.

[DGJP04] Josee Desharnais, Vineet Gupta, Radha Jagadeesan, and Prakash Panangaden. Metrics for labelled markov processes. *Theor. Comput. Sci.*, 318(3):323–354, 2004.

[GcJS90] Alessandro Giacalone, Chi chang Jou, and Scott A. Smolka. Algebraic reasoning for probabilistic concurrent systems. In *Proc. IFIP TC2 Working Conference on Programming Concepts and Methods*, pages 443–458. North-Holland, 1990.

[JL91] Bengt Jonsson and Kim Guldstrand Larsen. Specification and refinement of probabilistic processes. In *LICS*, pages 266–277, 1991.

[Kan42] L. Kantorovich. On the transfer of masses (in Russian). *Doklady Akademii Nauk*, 37(2):227–229, 1942. Translated in *Management Science*, 5:1-4, 1959.

[KR58] L.V. Kantorovich and G.Sh. Rubinstein. On the space of completely additive functions. *Vestnik Leningradskogo Universiteta*, 3(2):52–59, 1958. In Russian.

[LS91] Kim Guldstrand Larsen and Arne Skou. Bisimulation through probabilistic testing. *Inf. Comput.*, 94(1):1–28, 1991.

[Pan09] Prakash Panangaden. *Labelled Markov Processes*. Imperial College Press, 2009.

[Sch10] Alexander Schrijver. *A Course in Combinatorial Optimization*. Course notes, available at http://homepages.cwi.nl/~lex/, 2010.

[SL95] Roberto Segala and Nancy A. Lynch. Probabilistic simulations for probabilistic processes. *Nord. J. Comput.*, 2(2):250–273, 1995.

[vBSW07] Franck van Breugel, Babita Sharma, and James Worrell. Approximating a behavioural pseudometric without discount for probabilistic systems. In *FoSSaCS*, pages 123–137, 2007.

[vBW01a] Franck van Breugel and James Worrell. An algorithm for quantitative verification of probabilistic transition systems. In *CONCUR*, pages 336–350, 2001.

[vBW01b] Franck van Breugel and James Worrell. Towards quantitative verification of probabilistic transition systems. In *ICALP*, pages 421–432, 2001.

Aachener Informatik-Berichte

This is the list of all technical reports since 1987. To obtain copies of reports please consult

http://aib.informatik.rwth-aachen.de/

or send your request to:

Informatik-Bibliothek, RWTH Aachen, Ahornstr. 55, 52056 Aachen,
Email: biblio@informatik.rwth-aachen.de

1987-01 * Fachgruppe Informatik: Jahresbericht 1986

1987-02 * David de Frutos Escrig, Klaus Indermark: Equivalence Relations of Non-Deterministic Ianov-Schemes

1987-03 * Manfred Nagl: A Software Development Environment based on Graph Technology

1987-04 * Claus Lewerentz, Manfred Nagl, Bernhard Westfechtel: On Integration Mechanisms within a Graph-Based Software Development Environment

1987-05 * Reinhard Rinn: Über Eingabeanomalien bei verschiedenen Inferenzmodellen

1987-06 * Werner Damm, Gert Döhmen: Specifying Distributed Computer Architectures in AADL*

1987-07 * Gregor Engels, Claus Lewerentz, Wilhelm Schäfer: Graph Grammar Engineering: A Software Specification Method

1987-08 * Manfred Nagl: Set Theoretic Approaches to Graph Grammars

1987-09 * Claus Lewerentz, Andreas Schürr: Experiences with a Database System for Software Documents

1987-10 * Herbert Klaeren, Klaus Indermark: A New Implementation Technique for Recursive Function Definitions

1987-11 * Rita Loogen: Design of a Parallel Programmable Graph Reduction Machine with Distributed Memory

1987-12 J. Börstler, U. Möncke, R. Wilhelm: Table compression for tree automata

1988-01 * Gabriele Esser, Johannes Rückert, Frank Wagner Gesellschaftliche Aspekte der Informatik

1988-02 * Peter Martini, Otto Spaniol: Token-Passing in High-Speed Backbone Networks for Campus-Wide Environments

1988-03 * Thomas Welzel: Simulation of a Multiple Token Ring Backbone

1988-04 * Peter Martini: Performance Comparison for HSLAN Media Access Protocols

1988-05 * Peter Martini: Performance Analysis of Multiple Token Rings

1988-06 * Andreas Mann, Johannes Rückert, Otto Spaniol: Datenfunknetze

1988-07 * Andreas Mann, Johannes Rückert: Packet Radio Networks for Data Exchange

1988-08 * Andreas Mann, Johannes Rückert: Concurrent Slot Assignment Protocol for Packet Radio Networks

1988-09 * W. Kremer, F. Reichert, J. Rückert, A. Mann: Entwurf einer Netzwerktopologie für ein Mobilfunknetz zur Unterstützung des öffentlichen Straßenverkehrs

1988-10 * Kai Jakobs: Towards User-Friendly Networking

1988-11 * Kai Jakobs: The Directory - Evolution of a Standard

1988-12 * Kai Jakobs: Directory Services in Distributed Systems - A Survey

1988-13 * Martine Schümmer: RS-511, a Protocol for the Plant Floor

1988-14 * U. Quernheim: Satellite Communication Protocols - A Performance Comparison Considering On-Board Processing

1988-15 * Peter Martini, Otto Spaniol, Thomas Welzel: File Transfer in High Speed Token Ring Networks: Performance Evaluation by Approximate Analysis and Simulation

1988-16 * Fachgruppe Informatik: Jahresbericht 1987

1988-17 * Wolfgang Thomas: Automata on Infinite Objects

1988-18 * Michael Sonnenschein: On Petri Nets and Data Flow Graphs

1988-19 * Heiko Vogler: Functional Distribution of the Contextual Analysis in Block-Structured Programming Languages: A Case Study of Tree Transducers

1988-20 * Thomas Welzel: Einsatz des Simulationswerkzeuges QNAP2 zur Leistungsbewertung von Kommunikationsprotokollen

1988-21 * Th. Janning, C. Lewerentz: Integrated Project Team Management in a Software Development Environment

1988-22 * Joost Engelfriet, Heiko Vogler: Modular Tree Transducers

1988-23 * Wolfgang Thomas: Automata and Quantifier Hierarchies

1988-24 * Uschi Heuter: Generalized Definite Tree Languages

1989-01 * Fachgruppe Informatik: Jahresbericht 1988

1989-02 * G. Esser, J. Rückert, F. Wagner (Hrsg.): Gesellschaftliche Aspekte der Informatik

1989-03 * Heiko Vogler: Bottom-Up Computation of Primitive Recursive Tree Functions

1989-04 * Andy Schürr: Introduction to PROGRESS, an Attribute Graph Grammar Based Specification Language

1989-05 J. Börstler: Reuse and Software Development - Problems, Solutions, and Bibliography (in German)

1989-06 * Kai Jakobs: OSI - An Appropriate Basis for Group Communication?

1989-07 * Kai Jakobs: ISO's Directory Proposal - Evolution, Current Status and Future Problems

1989-08 * Bernhard Westfechtel: Extension of a Graph Storage for Software Documents with Primitives for Undo/Redo and Revision Control

1989-09 * Peter Martini: High Speed Local Area Networks - A Tutorial

1989-10 * P. Davids, Th. Welzel: Performance Analysis of DQDB Based on Simulation

1989-11 * Manfred Nagl (Ed.): Abstracts of Talks presented at the WG '89 15th International Workshop on Graphtheoretic Concepts in Computer Science

1989-12 * Peter Martini: The DQDB Protocol - Is it Playing the Game?

1989-13 * Martine Schümmer: CNC/DNC Communication with MAP

1989-14 * Martine Schümmer: Local Area Networks for Manufactoring Environments with hard Real-Time Requirements

1989-15 * M. Schümmer, Th. Welzel, P. Martini: Integration of Field Bus and MAP Networks - Hierarchical Communication Systems in Production Environments

1989-16 * G. Vossen, K.-U. Witt: SUXESS: Towards a Sound Unification of Extensions of the Relational Data Model

1989-17 * J. Derissen, P. Hruschka, M.v.d. Beeck, Th. Janning, M. Nagl: Integrating Structured Analysis and Information Modelling

1989-18 A. Maassen: Programming with Higher Order Functions

1989-19 * Mario Rodriguez-Artalejo, Heiko Vogler: A Narrowing Machine for Syntax Directed BABEL

1989-20 H. Kuchen, R. Loogen, J.J. Moreno Navarro, M. Rodriguez Artalejo: Graph-based Implementation of a Functional Logic Language

1990-01 * Fachgruppe Informatik: Jahresbericht 1989

1990-02 * Vera Jansen, Andreas Potthoff, Wolfgang Thomas, Udo Wermuth: A Short Guide to the AMORE System (Computing Automata, MOnoids and Regular Expressions)

1990-03 * Jerzy Skurczynski: On Three Hierarchies of Weak SkS Formulas

1990-04 R. Loogen: Stack-based Implementation of Narrowing

1990-05 H. Kuchen, A. Wagener: Comparison of Dynamic Load Balancing Strategies

1990-06 * Kai Jakobs, Frank Reichert: Directory Services for Mobile Communication

1990-07 * Kai Jakobs: What's Beyond the Interface - OSI Networks to Support Cooperative Work

1990-08 * Kai Jakobs: Directory Names and Schema - An Evaluation

1990-09 * Ulrich Quernheim, Dieter Kreuer: Das CCITT - Signalisierungssystem Nr. 7 auf Satellitenstrecken; Simulation der Zeichengabestrecke

1990-11 H. Kuchen, R. Loogen, J.J. Moreno Navarro, M. Rodriguez Artalejo: Lazy Narrowing in a Graph Machine

1990-12 * Kai Jakobs, Josef Kaltwasser, Frank Reichert, Otto Spaniol: Der Computer fährt mit

1990-13 * Rudolf Mathar, Andreas Mann: Analyzing a Distributed Slot Assignment Protocol by Markov Chains

1990-14 A. Maassen: Compilerentwicklung in Miranda - ein Praktikum in funktionaler Programmierung (written in german)

1990-15 * Manfred Nagl, Andreas Schürr: A Specification Environment for Graph Grammars

1990-16 A. Schürr: PROGRESS: A VHL-Language Based on Graph Grammars

1990-17 * Marita Möller: Ein Ebenenmodell wissensbasierter Konsultationen - Unterstützung für Wissensakquisition und Erklärungsfähigkeit

1990-18 * Eric Kowalewski: Entwurf und Interpretation einer Sprache zur Beschreibung von Konsultationsphasen in Expertensystemen

1990-20 Y. Ortega Mallen, D. de Frutos Escrig: A Complete Proof System for Timed Observations

1990-21 * Manfred Nagl: Modelling of Software Architectures: Importance, Notions, Experiences

1990-22 H. Fassbender, H. Vogler: A Call-by-need Implementation of Syntax Directed Functional Programming

1991-01 Guenther Geiler (ed.), Fachgruppe Informatik: Jahresbericht 1990

1991-03 B. Steffen, A. Ingolfsdottir: Characteristic Formulae for Processes with Divergence

1991-04 M. Portz: A new class of cryptosystems based on interconnection networks

1991-05 H. Kuchen, G. Geiler: Distributed Applicative Arrays

1991-06 * Ludwig Staiger: Kolmogorov Complexity and Hausdorff Dimension

1991-07 * Ludwig Staiger: Syntactic Congruences for w-languages

1991-09 * Eila Kuikka: A Proposal for a Syntax-Directed Text Processing System

1991-10 K. Gladitz, H. Fassbender, H. Vogler: Compiler-based Implementation of Syntax-Directed Functional Programming

1991-11 R. Loogen, St. Winkler: Dynamic Detection of Determinism in Functional Logic Languages

1991-12 * K. Indermark, M. Rodriguez Artalejo (Eds.): Granada Workshop on the Integration of Functional and Logic Programming

1991-13 * Rolf Hager, Wolfgang Kremer: The Adaptive Priority Scheduler: A More Fair Priority Service Discipline

1991-14 * Andreas Fasbender, Wolfgang Kremer: A New Approximation Algorithm for Tandem Networks with Priority Nodes

1991-15 J. Börstler, A. Zündorf: Revisiting extensions to Modula-2 to support reusability

1991-16 J. Börstler, Th. Janning: Bridging the gap between Requirements Analysis and Design

1991-17 A. Zündorf, A. Schürr: Nondeterministic Control Structures for Graph Rewriting Systems

1991-18 * Matthias Jarke, John Mylopoulos, Joachim W. Schmidt, Yannis Vassiliou: DAIDA: An Environment for Evolving Information Systems

1991-19 M. Jeusfeld, M. Jarke: From Relational to Object-Oriented Integrity Simplification

1991-20 G. Hogen, A. Kindler, R. Loogen: Automatic Parallelization of Lazy Functional Programs

1991-21 * Prof. Dr. rer. nat. Otto Spaniol: ODP (Open Distributed Processing): Yet another Viewpoint

1991-22 H. Kuchen, F. Lücking, H. Stoltze: The Topology Description Language TDL

1991-23 S. Graf, B. Steffen: Compositional Minimization of Finite State Systems

1991-24 R. Cleaveland, J. Parrow, B. Steffen: The Concurrency Workbench: A Semantics Based Tool for the Verification of Concurrent Systems

1991-25 * Rudolf Mathar, Jürgen Mattfeldt: Optimal Transmission Ranges for Mobile Communication in Linear Multihop Packet Radio Networks

1991-26 M. Jeusfeld, M. Staudt: Query Optimization in Deductive Object Bases

1991-27 J. Knoop, B. Steffen: The Interprocedural Coincidence Theorem

1991-28 J. Knoop, B. Steffen: Unifying Strength Reduction and Semantic Code Motion

1991-30 T. Margaria: First-Order theories for the verification of complex FSMs

1991-31 B. Steffen: Generating Data Flow Analysis Algorithms from Modal Specifications

1992-01 Stefan Eherer (ed.), Fachgruppe Informatik: Jahresbericht 1991

1992-02 * Bernhard Westfechtel: Basismechanismen zur Datenverwaltung in strukturbezogenen Hypertextsystemen

1992-04 S. A. Smolka, B. Steffen: Priority as Extremal Probability

1992-05 * Matthias Jarke, Carlos Maltzahn, Thomas Rose: Sharing Processes: Team Coordination in Design Repositories

1992-06 O. Burkart, B. Steffen: Model Checking for Context-Free Processes

1992-07 * Matthias Jarke, Klaus Pohl: Information Systems Quality and Quality Information Systems

1992-08 * Rudolf Mathar, Jürgen Mattfeldt: Analyzing Routing Strategy NFP in Multihop Packet Radio Networks on a Line

1992-09 * Alfons Kemper, Guido Moerkotte: Grundlagen objektorientierter Datenbanksysteme

1992-10 Matthias Jarke, Manfred Jeusfeld, Andreas Miethsam, Michael Gocek: Towards a logic-based reconstruction of software configuration management

1992-11 Werner Hans: A Complete Indexing Scheme for WAM-based Abstract Machines

1992-12 W. Hans, R. Loogen, St. Winkler: On the Interaction of Lazy Evaluation and Backtracking

1992-13 * Matthias Jarke, Thomas Rose: Specification Management with CAD

1992-14 Th. Noll, H. Vogler: Top-down Parsing with Simultaneous Evaluation on Noncircular Attribute Grammars

1992-15 A. Schuerr, B. Westfechtel: Graphgrammatiken und Graphersetzungssysteme(written in german)

1992-16 * Graduiertenkolleg Informatik und Technik (Hrsg.): Forschungsprojekte des Graduiertenkollegs Informatik und Technik

1992-17 M. Jarke (ed.): ConceptBase V3.1 User Manual

1992-18 * Clarence A. Ellis, Matthias Jarke (Eds.): Distributed Cooperation in Integrated Information Systems - Proceedings of the Third International Workshop on Intelligent and Cooperative Information Systems

1992-19-00 H. Kuchen, R. Loogen (eds.): Proceedings of the 4th Int. Workshop on the Parallel Implementation of Functional Languages

1992-19-01 G. Hogen, R. Loogen: PASTEL - A Parallel Stack-Based Implementation of Eager Functional Programs with Lazy Data Structures (Extended Abstract)

1992-19-02 H. Kuchen, K. Gladitz: Implementing Bags on a Shared Memory MIMD-Machine

1992-19-03 C. Rathsack, S.B. Scholz: LISA - A Lazy Interpreter for a Full-Fledged Lambda-Calculus

1992-19-04 T.A. Bratvold: Determining Useful Parallelism in Higher Order Functions

1992-19-05 S. Kahrs: Polymorphic Type Checking by Interpretation of Code

1992-19-06 M. Chakravarty, M. Köhler: Equational Constraints, Residuation, and the Parallel JUMP-Machine

1992-19-07 J. Seward: Polymorphic Strictness Analysis using Frontiers (Draft Version)

1992-19-08 D. Gärtner, A. Kimms, W. Kluge: pi-Redˆ+ - A Compiling Graph-Reduction System for a Full Fledged Lambda-Calculus

1992-19-09 D. Howe, G. Burn: Experiments with strict STG code

1992-19-10 J. Glauert: Parallel Implementation of Functional Languages Using Small Processes

1992-19-11 M. Joy, T. Axford: A Parallel Graph Reduction Machine

1992-19-12 A. Bennett, P. Kelly: Simulation of Multicache Parallel Reduction

1992-19-13 K. Langendoen, D.J. Agterkamp: Cache Behaviour of Lazy Functional Programs (Working Paper)

1992-19-14 K. Hammond, S. Peyton Jones: Profiling scheduling strategies on the GRIP parallel reducer

1992-19-15 S. Mintchev: Using Strictness Information in the STG-machine

1992-19-16 D. Rushall: An Attribute Grammar Evaluator in Haskell

1992-19-17 J. Wild, H. Glaser, P. Hartel: Statistics on storage management in a lazy functional language implementation

1992-19-18 W.S. Martins: Parallel Implementations of Functional Languages

1992-19-19 D. Lester: Distributed Garbage Collection of Cyclic Structures (Draft version)

1992-19-20 J.C. Glas, R.F.H. Hofman, W.G. Vree: Parallelization of Branch-and-Bound Algorithms in a Functional Programming Environment

1992-19-21 S. Hwang, D. Rushall: The nu-STG machine: a parallelized Spineless Tagless Graph Reduction Machine in a distributed memory architecture (Draft version)

1992-19-22 G. Burn, D. Le Metayer: Cps-Translation and the Correctness of Optimising Compilers

1992-19-23 S.L. Peyton Jones, P. Wadler: Imperative functional programming (Brief summary)

1992-19-24 W. Damm, F. Liu, Th. Peikenkamp: Evaluation and Parallelization of Functions in Functional + Logic Languages (abstract)

1992-19-25 M. Kesseler: Communication Issues Regarding Parallel Functional Graph Rewriting

1992-19-26 Th. Peikenkamp: Charakterizing and representing neededness in functional loginc languages (abstract)

1992-19-27 H. Doerr: Monitoring with Graph-Grammars as formal operational Models

1992-19-28 J. van Groningen: Some implementation aspects of Concurrent Clean on distributed memory architectures

1992-19-29 G. Ostheimer: Load Bounding for Implicit Parallelism (abstract)

1992-20 H. Kuchen, F.J. Lopez Fraguas, J.J. Moreno Navarro, M. Rodriguez Artalejo: Implementing Disequality in a Lazy Functional Logic Language

1992-21 H. Kuchen, F.J. Lopez Fraguas: Result Directed Computing in a Functional Logic Language

1992-22 H. Kuchen, J.J. Moreno Navarro, M.V. Hermenegildo: Independent AND-Parallel Narrowing

1992-23 T. Margaria, B. Steffen: Distinguishing Formulas for Free

1992-24 K. Pohl: The Three Dimensions of Requirements Engineering

1992-25 * R. Stainov: A Dynamic Configuration Facility for Multimedia Communications

1992-26 * Michael von der Beeck: Integration of Structured Analysis and Timed Statecharts for Real-Time and Concurrency Specification

1992-27 W. Hans, St. Winkler: Aliasing and Groundness Analysis of Logic Programs through Abstract Interpretation and its Safety

1992-28 * Gerhard Steinke, Matthias Jarke: Support for Security Modeling in Information Systems Design

1992-29 B. Schinzel: Warum Frauenforschung in Naturwissenschaft und Technik

1992-30 A. Kemper, G. Moerkotte, K. Peithner: Object-Orientation Axiomatised by Dynamic Logic

1992-32 * Bernd Heinrichs, Kai Jakobs: Timer Handling in High-Performance Transport Systems

1992-33 * B. Heinrichs, K. Jakobs, K. Lenßen, W. Reinhardt, A. Spinner: EuroBridge: Communication Services for Multimedia Applications

1992-34 C. Gerlhof, A. Kemper, Ch. Kilger, G. Moerkotte: Partition-Based Clustering in Object Bases: From Theory to Practice

1992-35 J. Börstler: Feature-Oriented Classification and Reuse in IPSEN

1992-36 M. Jarke, J. Bubenko, C. Rolland, A. Sutcliffe, Y. Vassiliou: Theories Underlying Requirements Engineering: An Overview of NATURE at Genesis

1992-37 * K. Pohl, M. Jarke: Quality Information Systems: Repository Support for Evolving Process Models

1992-38 A. Zuendorf: Implementation of the imperative / rule based language PROGRES

1992-39 P. Koch: Intelligentes Backtracking bei der Auswertung funktional-logischer Programme

1992-40 * Rudolf Mathar, Jürgen Mattfeldt: Channel Assignment in Cellular Radio Networks

1992-41 * Gerhard Friedrich, Wolfgang Neidl: Constructive Utility in Model-Based Diagnosis Repair Systems

1992-42 * P. S. Chen, R. Hennicker, M. Jarke: On the Retrieval of Reusable Software Components

1992-43 W. Hans, St.Winkler: Abstract Interpretation of Functional Logic Languages

1992-44 N. Kiesel, A. Schuerr, B. Westfechtel: Design and Evaluation of GRAS, a Graph-Oriented Database System for Engineering Applications

1993-01 * Fachgruppe Informatik: Jahresbericht 1992

1993-02 * Patrick Shicheng Chen: On Inference Rules of Logic-Based Information Retrieval Systems

1993-03 G. Hogen, R. Loogen: A New Stack Technique for the Management of Runtime Structures in Distributed Environments

1993-05 A. Zündorf: A Heuristic for the Subgraph Isomorphism Problem in Executing PROGRES

1993-06 A. Kemper, D. Kossmann: Adaptable Pointer Swizzling Strategies in Object Bases: Design, Realization, and Quantitative Analysis

1993-07 * Graduiertenkolleg Informatik und Technik (Hrsg.): Graduiertenkolleg Informatik und Technik

1993-08 * Matthias Berger: k-Coloring Vertices using a Neural Network with Convergence to Valid Solutions

1993-09 M. Buchheit, M. Jeusfeld, W. Nutt, M. Staudt: Subsumption between Queries to Object-Oriented Databases

1993-10 O. Burkart, B. Steffen: Pushdown Processes: Parallel Composition and Model Checking

1993-11 * R. Große-Wienker, O. Hermanns, D. Menzenbach, A. Pollacks, S. Repetzki, J. Schwartz, K. Sonnenschein, B. Westfechtel: Das SUKITS-Projekt: A-posteriori-Integration heterogener CIM-Anwendungssysteme

1993-12 * Rudolf Mathar, Jürgen Mattfeldt: On the Distribution of Cumulated Interference Power in Rayleigh Fading Channels

1993-13 O. Maler, L. Staiger: On Syntactic Congruences for omega-languages

1993-14 M. Jarke, St. Eherer, R. Gallersdoerfer, M. Jeusfeld, M. Staudt: ConceptBase - A Deductive Object Base Manager

1993-15 M. Staudt, H.W. Nissen, M.A. Jeusfeld: Query by Class, Rule and Concept

1993-16 * M. Jarke, K. Pohl, St. Jacobs et al.: Requirements Engineering: An Integrated View of Representation Process and Domain

1993-17 * M. Jarke, K. Pohl: Establishing Vision in Context: Towards a Model of Requirements Processes

1993-18 W. Hans, H. Kuchen, St. Winkler: Full Indexing for Lazy Narrowing

1993-19 W. Hans, J.J. Ruz, F. Saenz, St. Winkler: A VHDL Specification of a Shared Memory Parallel Machine for Babel

1993-20 * K. Finke, M. Jarke, P. Szczurko, R. Soltysiak: Quality Management for Expert Systems in Process Control

1993-21 M. Jarke, M.A. Jeusfeld, P. Szczurko: Three Aspects of Intelligent Cooperation in the Quality Cycle

1994-01 Margit Generet, Sven Martin (eds.), Fachgruppe Informatik: Jahresbericht 1993

1994-02 M. Lefering: Development of Incremental Integration Tools Using Formal Specifications

1994-03 * P. Constantopoulos, M. Jarke, J. Mylopoulos, Y. Vassiliou: The Software Information Base: A Server for Reuse

1994-04 * Rolf Hager, Rudolf Mathar, Jürgen Mattfeldt: Intelligent Cruise Control and Reliable Communication of Mobile Stations

1994-05 * Rolf Hager, Peter Hermesmann, Michael Portz: Feasibility of Authentication Procedures within Advanced Transport Telematics

1994-06 * Claudia Popien, Bernd Meyer, Axel Kuepper: A Formal Approach to Service Import in ODP Trader Federations

1994-07 P. Peters, P. Szczurko: Integrating Models of Quality Management Methods by an Object-Oriented Repository

1994-08 * Manfred Nagl, Bernhard Westfechtel: A Universal Component for the Administration in Distributed and Integrated Development Environments

1994-09 * Patrick Horster, Holger Petersen: Signatur- und Authentifikationsverfahren auf der Basis des diskreten Logarithmusproblems

1994-11 A. Schürr: PROGRES, A Visual Language and Environment for PROgramming with Graph REwrite Systems

1994-12 A. Schürr: Specification of Graph Translators with Triple Graph Grammars

1994-13 A. Schürr: Logic Based Programmed Structure Rewriting Systems

1994-14 L. Staiger: Codes, Simplifying Words, and Open Set Condition

1994-15 * Bernhard Westfechtel: A Graph-Based System for Managing Configurations of Engineering Design Documents

1994-16 P. Klein: Designing Software with Modula-3

1994-17 I. Litovsky, L. Staiger: Finite acceptance of infinite words

1994-18 G. Hogen, R. Loogen: Parallel Functional Implementations: Graphbased vs. Stackbased Reduction

1994-19 M. Jeusfeld, U. Johnen: An Executable Meta Model for Re-Engineering of Database Schemas

1994-20 * R. Gallersdörfer, M. Jarke, K. Klabunde: Intelligent Networks as a Data Intensive Application (INDIA)

1994-21 M. Mohnen: Proving the Correctness of the Static Link Technique Using Evolving Algebras

1994-22 H. Fernau, L. Staiger: Valuations and Unambiguity of Languages, with Applications to Fractal Geometry

1994-24 * M. Jarke, K. Pohl, R. Dömges, St. Jacobs, H. W. Nissen: Requirements Information Management: The NATURE Approach

1994-25 * M. Jarke, K. Pohl, C. Rolland, J.-R. Schmitt: Experience-Based Method Evaluation and Improvement: A Process Modeling Approach

1994-26 * St. Jacobs, St. Kethers: Improving Communication and Decision Making within Quality Function Deployment

1994-27 * M. Jarke, H. W. Nissen, K. Pohl: Tool Integration in Evolving Information Systems Environments

1994-28 O. Burkart, D. Caucal, B. Steffen: An Elementary Bisimulation Decision Procedure for Arbitrary Context-Free Processes

1995-01 * Fachgruppe Informatik: Jahresbericht 1994

1995-02 Andy Schürr, Andreas J. Winter, Albert Zündorf: Graph Grammar Engineering with PROGRES

1995-03 Ludwig Staiger: A Tight Upper Bound on Kolmogorov Complexity by Hausdorff Dimension and Uniformly Optimal Prediction

1995-04 Birgitta König-Ries, Sven Helmer, Guido Moerkotte: An experimental study on the complexity of left-deep join ordering problems for cyclic queries

1995-05 Sophie Cluet, Guido Moerkotte: Efficient Evaluation of Aggregates on Bulk Types

1995-06 Sophie Cluet, Guido Moerkotte: Nested Queries in Object Bases

1995-07 Sophie Cluet, Guido Moerkotte: Query Optimization Techniques Exploiting Class Hierarchies

1995-08 Markus Mohnen: Efficient Compile-Time Garbage Collection for Arbitrary Data Structures

1995-09 Markus Mohnen: Functional Specification of Imperative Programs: An Alternative Point of View of Functional Languages

1995-10 Rainer Gallersdörfer, Matthias Nicola: Improving Performance in Replicated Databases through Relaxed Coherency

1995-11 * M.Staudt, K.von Thadden: Subsumption Checking in Knowledge Bases

1995-12 * G.V.Zemanek, H.W.Nissen, H.Hubert, M.Jarke: Requirements Analysis from Multiple Perspectives: Experiences with Conceptual Modeling Technology

1995-13 * M.Staudt, M.Jarke: Incremental Maintenance of Externally Materialized Views

1995-14 * P.Peters, P.Szczurko, M.Jeusfeld: Oriented Information Management: Conceptual Models at Work

1995-15 * Matthias Jarke, Sudha Ram (Hrsg.): WITS 95 Proceedings of the 5th Annual Workshop on Information Technologies and Systems

1995-16 * W.Hans, St.Winkler, F.Saenz: Distributed Execution in Functional Logic Programming

1996-01 * Jahresbericht 1995

1996-02 Michael Hanus, Christian Prehofer: Higher-Order Narrowing with Definitional Trees

1996-03 * W.Scheufele, G.Moerkotte: Optimal Ordering of Selections and Joins in Acyclic Queries with Expensive Predicates

1996-04 Klaus Pohl: PRO-ART: Enabling Requirements Pre-Traceability

1996-05 Klaus Pohl: Requirements Engineering: An Overview

1996-06 * M.Jarke, W.Marquardt: Design and Evaluation of Computer–Aided Process Modelling Tools

1996-07 Olaf Chitil: The Sigma-Semantics: A Comprehensive Semantics for Functional Programs

1996-08 * S.Sripada: On Entropy and the Limitations of the Second Law of Thermodynamics

1996-09 Michael Hanus (Ed.): Proceedings of the Poster Session of ALP96 - Fifth International Conference on Algebraic and Logic Programming

1996-09-0 Michael Hanus (Ed.): Proceedings of the Poster Session of ALP 96 - Fifth International Conference on Algebraic and Logic Programming: Introduction and table of contents

1996-09-1 Ilies Alouini: An Implementation of Conditional Concurrent Rewriting on Distributed Memory Machines

1996-09-2 Olivier Danvy, Karoline Malmkjær: On the Idempotence of the CPS Transformation

1996-09-3 Víctor M. Gulías, José L. Freire: Concurrent Programming in Haskell

1996-09-4 Sébastien Limet, Pierre Réty: On Decidability of Unifiability Modulo Rewrite Systems

1996-09-5 Alexandre Tessier: Declarative Debugging in Constraint Logic Programming

1996-10 Reidar Conradi, Bernhard Westfechtel: Version Models for Software Configuration Management

1996-11 * C.Weise, D.Lenzkes: A Fast Decision Algorithm for Timed Refinement

1996-12 * R.Dömges, K.Pohl, M.Jarke, B.Lohmann, W.Marquardt: PRO-ART/CE* — An Environment for Managing the Evolution of Chemical Process Simulation Models

1996-13 * K.Pohl, R.Klamma, K.Weidenhaupt, R.Dömges, P.Haumer, M.Jarke: A Framework for Process-Integrated Tools

1996-14 * R.Gallersdörfer, K.Klabunde, A.Stolz, M.Eßmajor: INDIA — Intelligent Networks as a Data Intensive Application, Final Project Report, June 1996

1996-15 * H.Schimpe, M.Staudt: VAREX: An Environment for Validating and Refining Rule Bases

1996-16 * M.Jarke, M.Gebhardt, S.Jacobs, H.Nissen: Conflict Analysis Across Heterogeneous Viewpoints: Formalization and Visualization

1996-17 Manfred A. Jeusfeld, Tung X. Bui: Decision Support Components on the Internet

1996-18 Manfred A. Jeusfeld, Mike Papazoglou: Information Brokering: Design, Search and Transformation

1996-19 * P.Peters, M.Jarke: Simulating the impact of information flows in networked organizations

1996-20 Matthias Jarke, Peter Peters, Manfred A. Jeusfeld: Model-driven planning and design of cooperative information systems

1996-21 * G.de Michelis, E.Dubois, M.Jarke, F.Matthes, J.Mylopoulos, K.Pohl, J.Schmidt, C.Woo, E.Yu: Cooperative information systems: a manifesto

1996-22 * S.Jacobs, M.Gebhardt, S.Kethers, W.Rzasa: Filling HTML forms simultaneously: CoWeb architecture and functionality

1996-23 * M.Gebhardt, S.Jacobs: Conflict Management in Design

1997-01 Michael Hanus, Frank Zartmann (eds.): Jahresbericht 1996

1997-02 Johannes Faassen: Using full parallel Boltzmann Machines for Optimization

1997-03 Andreas Winter, Andy Schürr: Modules and Updatable Graph Views for PROgrammed Graph REwriting Systems

1997-04 Markus Mohnen, Stefan Tobies: Implementing Context Patterns in the Glasgow Haskell Compiler

1997-05 * S.Gruner: Schemakorrespondenzaxiome unterstützen die paargrammatische Spezifikation inkrementeller Integrationswerkzeuge

1997-06 Matthias Nicola, Matthias Jarke: Design and Evaluation of Wireless Health Care Information Systems in Developing Countries

1997-07 Petra Hofstedt: Taskparallele Skelette für irregulär strukturierte Probleme in deklarativen Sprachen

1997-08 Dorothea Blostein, Andy Schürr: Computing with Graphs and Graph Rewriting

1997-09 Carl-Arndt Krapp, Bernhard Westfechtel: Feedback Handling in Dynamic Task Nets

1997-10 Matthias Nicola, Matthias Jarke: Integrating Replication and Communication in Performance Models of Distributed Databases

1997-11 * R. Klamma, P. Peters, M. Jarke: Workflow Support for Failure Management in Federated Organizations

1997-13 Markus Mohnen: Optimising the Memory Management of Higher-Order Functional Programs

1997-14 Roland Baumann: Client/Server Distribution in a Structure-Oriented Database Management System

1997-15 George Botorog: High-Level Parallel Programming and the Efficient Implementation of Numerical Algorithms

1998-01 * Fachgruppe Informatik: Jahresbericht 1997

1998-02 Stefan Gruner, Manfred Nagel, Andy Schürr: Fine-grained and Structure-Oriented Document Integration Tools are Needed for Development Processes

1998-03 Stefan Gruner: Einige Anmerkungen zur graphgrammatischen Spezifikation von Integrationswerkzeugen nach Westfechtel, Janning, Lefering und Schürr

1998-04 * O. Kubitz: Mobile Robots in Dynamic Environments

1998-05 Martin Leucker, Stephan Tobies: Truth - A Verification Platform for Distributed Systems

1998-06 * Matthias Oliver Berger: DECT in the Factory of the Future

1998-07 M. Arnold, M. Erdmann, M. Glinz, P. Haumer, R. Knoll, B. Paech, K. Pohl, J. Ryser, R. Studer, K. Weidenhaupt: Survey on the Scenario Use in Twelve Selected Industrial Projects

1998-09 * Th. Lehmann: Geometrische Ausrichtung medizinischer Bilder am Beispiel intraoraler Radiographien

1998-10 * M. Nicola, M. Jarke: Performance Modeling of Distributed and Replicated Databases

1998-11 * Ansgar Schleicher, Bernhard Westfechtel, Dirk Jäger: Modeling Dynamic Software Processes in UML

1998-12 * W. Appelt, M. Jarke: Interoperable Tools for Cooperation Support using the World Wide Web

1998-13 Klaus Indermark: Semantik rekursiver Funktionsdefinitionen mit Striktheitsinformation

1999-01 * Jahresbericht 1998

1999-02 * F. Huch: Verifcation of Erlang Programs using Abstract Interpretation and Model Checking — Extended Version

1999-03 * R. Gallersdörfer, M. Jarke, M. Nicola: The ADR Replication Manager

1999-04 María Alpuente, Michael Hanus, Salvador Lucas, Germán Vidal: Specialization of Functional Logic Programs Based on Needed Narrowing

1999-05 * W. Thomas (Ed.): DLT 99 - Developments in Language Theory Fourth International Conference

1999-06 * Kai Jakobs, Klaus-Dieter Kleefeld: Informationssysteme für die angewandte historische Geographie

1999-07 Thomas Wilke: CTL+ is exponentially more succinct than CTL

1999-08 Oliver Matz: Dot-Depth and Monadic Quantifier Alternation over Pictures

2000-01 * Jahresbericht 1999

2000-02 Jens Vöge, Marcin Jurdzinski A Discrete Strategy Improvement Algorithm for Solving Parity Games

2000-03 D. Jäger, A. Schleicher, B. Westfechtel: UPGRADE: A Framework for Building Graph-Based Software Engineering Tools

2000-04 Andreas Becks, Stefan Sklorz, Matthias Jarke: Exploring the Semantic Structure of Technical Document Collections: A Cooperative Systems Approach

2000-05 Mareike Schoop: Cooperative Document Management

2000-06 Mareike Schoop, Christoph Quix (eds.): Proceedings of the Fifth International Workshop on the Language-Action Perspective on Communication Modelling

2000-07 * Markus Mohnen, Pieter Koopman (Eds.): Proceedings of the 12th International Workshop of Functional Languages

2000-08 Thomas Arts, Thomas Noll: Verifying Generic Erlang Client-Server Implementations

2001-01 * Jahresbericht 2000

2001-02 Benedikt Bollig, Martin Leucker: Deciding LTL over Mazurkiewicz Traces

2001-03 Thierry Cachat: The power of one-letter rational languages

2001-04 Benedikt Bollig, Martin Leucker, Michael Weber: Local Parallel Model Checking for the Alternation Free mu-Calculus

2001-05 Benedikt Bollig, Martin Leucker, Thomas Noll: Regular MSC Languages

2001-06 Achim Blumensath: Prefix-Recognisable Graphs and Monadic Second-Order Logic

2001-07 Martin Grohe, Stefan Wöhrle: An Existential Locality Theorem

2001-08 Mareike Schoop, James Taylor (eds.): Proceedings of the Sixth International Workshop on the Language-Action Perspective on Communication Modelling

2001-09 Thomas Arts, Jürgen Giesl: A collection of examples for termination of term rewriting using dependency pairs

2001-10 Achim Blumensath: Axiomatising Tree-interpretable Structures

2001-11 Klaus Indermark, Thomas Noll (eds.): Kolloquium Programmiersprachen und Grundlagen der Programmierung

2002-01 * Jahresbericht 2001

2002-02 Jürgen Giesl, Aart Middeldorp: Transformation Techniques for Context-Sensitive Rewrite Systems

2002-03 Benedikt Bollig, Martin Leucker, Thomas Noll: Generalised Regular MSC Languages

2002-04 Jürgen Giesl, Aart Middeldorp: Innermost Termination of Context-Sensitive Rewriting

2002-05 Horst Lichter, Thomas von der Maßen, Thomas Weiler: Modelling Requirements and Architectures for Software Product Lines

2002-06 Henry N. Adorna: 3-Party Message Complexity is Better than 2-Party Ones for Proving Lower Bounds on the Size of Minimal Nondeterministic Finite Automata

2002-07 Jörg Dahmen: Invariant Image Object Recognition using Gaussian Mixture Densities

2002-08 Markus Mohnen: An Open Framework for Data-Flow Analysis in Java

2002-09 Markus Mohnen: Interfaces with Default Implementations in Java

2002-10 Martin Leucker: Logics for Mazurkiewicz traces

2002-11 Jürgen Giesl, Hans Zantema: Liveness in Rewriting

2003-01 * Jahresbericht 2002

2003-02 Jürgen Giesl, René Thiemann: Size-Change Termination for Term Rewriting

2003-03 Jürgen Giesl, Deepak Kapur: Deciding Inductive Validity of Equations

2003-04 Jürgen Giesl, René Thiemann, Peter Schneider-Kamp, Stephan Falke: Improving Dependency Pairs

2003-05 Christof Löding, Philipp Rohde: Solving the Sabotage Game is PSPACE-hard

2003-06 Franz Josef Och: Statistical Machine Translation: From Single-Word Models to Alignment Templates

2003-07 Horst Lichter, Thomas von der Maßen, Alexander Nyßen, Thomas Weiler: Vergleich von Ansätzen zur Feature Modellierung bei der Softwareproduktlinienentwicklung

2003-08 Jürgen Giesl, René Thiemann, Peter Schneider-Kamp, Stephan Falke: Mechanizing Dependency Pairs

2004-01 * Fachgruppe Informatik: Jahresbericht 2003

2004-02 Benedikt Bollig, Martin Leucker: Message-Passing Automata are expressively equivalent to EMSO logic

2004-03 Delia Kesner, Femke van Raamsdonk, Joe Wells (eds.): HOR 2004 – 2nd International Workshop on Higher-Order Rewriting

2004-04 Slim Abdennadher, Christophe Ringeissen (eds.): RULE 04 – Fifth International Workshop on Rule-Based Programming

2004-05 Herbert Kuchen (ed.): WFLP 04 – 13th International Workshop on Functional and (Constraint) Logic Programming

2004-06 Sergio Antoy, Yoshihito Toyama (eds.): WRS 04 – 4th International Workshop on Reduction Strategies in Rewriting and Programming

2004-07 Michael Codish, Aart Middeldorp (eds.): WST 04 – 7th International Workshop on Termination

2004-08 Klaus Indermark, Thomas Noll: Algebraic Correctness Proofs for Compiling Recursive Function Definitions with Strictness Information

2004-09 Joachim Kneis, Daniel Mölle, Stefan Richter, Peter Rossmanith: Parameterized Power Domination Complexity

2004-10 Zinaida Benenson, Felix C. Gärtner, Dogan Kesdogan: Secure Multi-Party Computation with Security Modules

2005-01 * Fachgruppe Informatik: Jahresbericht 2004

2005-02 Maximillian Dornseif, Felix C. Gärtner, Thorsten Holz, Martin Mink: An Offensive Approach to Teaching Information Security: "Aachen Summer School Applied IT Security"

2005-03 Jürgen Giesl, René Thiemann, Peter Schneider-Kamp: Proving and Disproving Termination of Higher-Order Functions

2005-04 Daniel Mölle, Stefan Richter, Peter Rossmanith: A Faster Algorithm for the Steiner Tree Problem

2005-05 Fabien Pouget, Thorsten Holz: A Pointillist Approach for Comparing Honeypots

2005-06 Simon Fischer, Berthold Vöcking: Adaptive Routing with Stale Information

2005-07 Felix C. Freiling, Thorsten Holz, Georg Wicherski: Botnet Tracking: Exploring a Root-Cause Methodology to Prevent Distributed Denial-of-Service Attacks

2005-08 Joachim Kneis, Peter Rossmanith: A New Satisfiability Algorithm With Applications To Max-Cut

2005-09 Klaus Kursawe, Felix C. Freiling: Byzantine Fault Tolerance on General Hybrid Adversary Structures

2005-10 Benedikt Bollig: Automata and Logics for Message Sequence Charts

2005-11 Simon Fischer, Berthold Vöcking: A Counterexample to the Fully Mixed Nash Equilibrium Conjecture

2005-12 Neeraj Mittal, Felix Freiling, S. Venkatesan, Lucia Draque Penso: Efficient Reductions for Wait-Free Termination Detection in Faulty Distributed Systems

2005-13 Carole Delporte-Gallet, Hugues Fauconnier, Felix C. Freiling: Revisiting Failure Detection and Consensus in Omission Failure Environments

2005-14 Felix C. Freiling, Sukumar Ghosh: Code Stabilization

2005-15 Uwe Naumann: The Complexity of Derivative Computation

2005-16 Uwe Naumann: Syntax-Directed Derivative Code (Part I: Tangent-Linear Code)

2005-17 Uwe Naumann: Syntax-directed Derivative Code (Part II: Intraprocedural Adjoint Code)

2005-18 Thomas von der Maßen, Klaus Müller, John MacGregor, Eva Geisberger, Jörg Dörr, Frank Houdek, Harbhajan Singh, Holger Wußmann, Hans-Veit Bacher, Barbara Paech: Einsatz von Features im Software-Entwicklungsprozess - Abschlußbericht des GI-Arbeitskreises "Features"

2005-19 Uwe Naumann, Andre Vehreschild: Tangent-Linear Code by Augmented LL-Parsers

2005-20 Felix C. Freiling, Martin Mink: Bericht über den Workshop zur Ausbildung im Bereich IT-Sicherheit Hochschulausbildung, berufliche Weiterbildung, Zertifizierung von Ausbildungsangeboten am 11. und 12. August 2005 in Köln organisiert von RWTH Aachen in Kooperation mit BITKOM, BSI, DLR und Gesellschaft fuer Informatik (GI) e.V.

2005-21 Thomas Noll, Stefan Rieger: Optimization of Straight-Line Code Revisited

2005-22 Felix Freiling, Maurice Herlihy, Lucia Draque Penso: Optimal Randomized Fair Exchange with Secret Shared Coins

2005-23 Heiner Ackermann, Alantha Newman, Heiko Röglin, Berthold Vöcking: Decision Making Based on Approximate and Smoothed Pareto Curves

2005-24 Alexander Becher, Zinaida Benenson, Maximillian Dornseif: Tampering with Motes: Real-World Physical Attacks on Wireless Sensor Networks

2006-01 * Fachgruppe Informatik: Jahresbericht 2005

2006-02 Michael Weber: Parallel Algorithms for Verification of Large Systems

2006-03 Michael Maier, Uwe Naumann: Intraprocedural Adjoint Code Generated by the Differentiation-Enabled NAGWare Fortran Compiler

2006-04 Ebadollah Varnik, Uwe Naumann, Andrew Lyons: Toward Low Static Memory Jacobian Accumulation

2006-05 Uwe Naumann, Jean Utke, Patrick Heimbach, Chris Hill, Derya Ozyurt, Carl Wunsch, Mike Fagan, Nathan Tallent, Michelle Strout: Adjoint Code by Source Transformation with OpenAD/F

2006-06 Joachim Kneis, Daniel Mölle, Stefan Richter, Peter Rossmanith: Divide-and-Color

2006-07 Thomas Colcombet, Christof Löding: Transforming structures by set interpretations

2006-08 Uwe Naumann, Yuxiao Hu: Optimal Vertex Elimination in Single-Expression-Use Graphs

2006-09 Tingting Han, Joost-Pieter Katoen: Counterexamples in Probabilistic Model Checking

2006-10 Mesut Günes, Alexander Zimmermann, Martin Wenig, Jan Ritzerfeld, Ulrich Meis: From Simulations to Testbeds - Architecture of the Hybrid MCG-Mesh Testbed

2006-11 Bastian Schlich, Michael Rohrbach, Michael Weber, Stefan Kowalewski: Model Checking Software for Microcontrollers

2006-12 Benedikt Bollig, Joost-Pieter Katoen, Carsten Kern, Martin Leucker: Replaying Play in and Play out: Synthesis of Design Models from Scenarios by Learning

2006-13 Wong Karianto, Christof Löding: Unranked Tree Automata with Sibling Equalities and Disequalities

2006-14 Danilo Beuche, Andreas Birk, Heinrich Dreier, Andreas Fleischmann, Heidi Galle, Gerald Heller, Dirk Janzen, Isabel John, Ramin Tavakoli Kolagari, Thomas von der Maßen, Andreas Wolfram: Report of the GI Work Group "Requirements Management Tools for Product Line Engineering"

2006-15 Sebastian Ullrich, Jakob T. Valvoda, Torsten Kuhlen: Utilizing optical sensors from mice for new input devices

2006-16 Rafael Ballagas, Jan Borchers: Selexels: a Conceptual Framework for Pointing Devices with Low Expressiveness

2006-17 Eric Lee, Henning Kiel, Jan Borchers: Scrolling Through Time: Improving Interfaces for Searching and Navigating Continuous Audio Timelines

2007-01 * Fachgruppe Informatik: Jahresbericht 2006

2007-02 Carsten Fuhs, Jürgen Giesl, Aart Middeldorp, Peter Schneider-Kamp, René Thiemann, and Harald Zankl: SAT Solving for Termination Analysis with Polynomial Interpretations

2007-03 Jürgen Giesl, René Thiemann, Stephan Swiderski, and Peter Schneider-Kamp: Proving Termination by Bounded Increase

2007-04 Jan Buchholz, Eric Lee, Jonathan Klein, and Jan Borchers: coJIVE: A System to Support Collaborative Jazz Improvisation

2007-05 Uwe Naumann: On Optimal DAG Reversal

2007-06 Joost-Pieter Katoen, Thomas Noll, and Stefan Rieger: Verifying Concurrent List-Manipulating Programs by LTL Model Checking

2007-07 Alexander Nyßen, Horst Lichter: MeDUSA - MethoD for UML2-based Design of Embedded Software Applications

2007-08 Falk Salewski and Stefan Kowalewski: Achieving Highly Reliable Embedded Software: An empirical evaluation of different approaches

2007-09 Tina Kraußer, Heiko Mantel, and Henning Sudbrock: A Probabilistic Justification of the Combining Calculus under the Uniform Scheduler Assumption

2007-10 Martin Neuhäußer, Joost-Pieter Katoen: Bisimulation and Logical Preservation for Continuous-Time Markov Decision Processes

2007-11 Klaus Wehrle (editor): 6. Fachgespräch Sensornetzwerke

2007-12 Uwe Naumann: An L-Attributed Grammar for Adjoint Code

2007-13 Uwe Naumann, Michael Maier, Jan Riehme, and Bruce Christianson: Second-Order Adjoints by Source Code Manipulation of Numerical Programs

2007-14 Jean Utke, Uwe Naumann, Mike Fagan, Nathan Tallent, Michelle Strout, Patrick Heimbach, Chris Hill, and Carl Wunsch: OpenAD/F: A Modular, Open-Source Tool for Automatic Differentiation of Fortran Codes

2007-15 Volker Stolz: Temporal assertions for sequential and concurrent programs

2007-16 Sadeq Ali Makram, Mesut Güneç, Martin Wenig, Alexander Zimmermann: Adaptive Channel Assignment to Support QoS and Load Balancing for Wireless Mesh Networks

2007-17 René Thiemann: The DP Framework for Proving Termination of Term Rewriting

2007-18 Uwe Naumann: Call Tree Reversal is NP-Complete

2007-19 Jan Riehme, Andrea Walther, Jörg Stiller, Uwe Naumann: Adjoints for Time-Dependent Optimal Control

2007-20 Joost-Pieter Katoen, Daniel Klink, Martin Leucker, and Verena Wolf: Three-Valued Abstraction for Probabilistic Systems

2007-21 Tingting Han, Joost-Pieter Katoen, and Alexandru Mereacre: Compositional Modeling and Minimization of Time-Inhomogeneous Markov Chains

2007-22 Heiner Ackermann, Paul W. Goldberg, Vahab S. Mirrokni, Heiko Röglin, and Berthold Vöcking: Uncoordinated Two-Sided Markets

2008-01 * Fachgruppe Informatik: Jahresbericht 2007

2008-02 Henrik Bohnenkamp, Marielle Stoelinga: Quantitative Testing

2008-03 Carsten Fuhs, Jürgen Giesl, Aart Middeldorp, Peter Schneider-Kamp, René Thiemann, Harald Zankl: Maximal Termination

2008-04 Uwe Naumann, Jan Riehme: Sensitivity Analysis in Sisyphe with the AD-Enabled NAGWare Fortran Compiler

2008-05 Frank G. Radmacher: An Automata Theoretic Approach to the Theory of Rational Tree Relations

2008-06 Uwe Naumann, Laurent Hascoet, Chris Hill, Paul Hovland, Jan Riehme, Jean Utke: A Framework for Proving Correctness of Adjoint Message Passing Programs

2008-07 Alexander Nyßen, Horst Lichter: The MeDUSA Reference Manual, Second Edition

2008-08 George B. Mertzios, Stavros D. Nikolopoulos: The λ-cluster Problem on Parameterized Interval Graphs

2008-09 George B. Mertzios, Walter Unger: An optimal algorithm for the k-fixed-endpoint path cover on proper interval graphs

2008-10 George B. Mertzios, Walter Unger: Preemptive Scheduling of Equal-Length Jobs in Polynomial Time

2008-11 George B. Mertzios: Fast Convergence of Routing Games with Splittable Flows

2008-12 Joost-Pieter Katoen, Daniel Klink, Martin Leucker, Verena Wolf: Abstraction for stochastic systems by Erlang's method of stages

2008-13 Beatriz Alarcón, Fabian Emmes, Carsten Fuhs, Jürgen Giesl, Raúl Gutiérrez, Salvador Lucas, Peter Schneider-Kamp, René Thiemann: Improving Context-Sensitive Dependency Pairs

2008-14 Bastian Schlich: Model Checking of Software for Microcontrollers

2008-15 Joachim Kneis, Alexander Langer, Peter Rossmanith: A New Algorithm for Finding Trees with Many Leaves

2008-16 Hendrik vom Lehn, Elias Weingärtner and Klaus Wehrle: Comparing recent network simulators: A performance evaluation study

2008-17 Peter Schneider-Kamp: Static Termination Analysis for Prolog using Term Rewriting and SAT Solving

2008-18 Falk Salewski: Empirical Evaluations of Safety-Critical Embedded Systems

2008-19 Dirk Wilking: Empirical Studies for the Application of Agile Methods to Embedded Systems

2009-02 Taolue Chen, Tingting Han, Joost-Pieter Katoen, Alexandru Mereacre: Quantitative Model Checking of Continuous-Time Markov Chains Against Timed Automata Specifications

2009-03 Alexander Nyßen: Model-Based Construction of Embedded Real-Time Software - A Methodology for Small Devices

2009-04 Daniel Klünder: Entwurf eingebetteter Software mit abstrakten Zustandsmaschinen und Business Object Notation

2009-05 George B. Mertzios, Ignasi Sau, Shmuel Zaks: A New Intersection Model and Improved Algorithms for Tolerance Graphs

2009-06 George B. Mertzios, Ignasi Sau, Shmuel Zaks: The Recognition of Tolerance and Bounded Tolerance Graphs is NP-complete

2009-07 Joachim Kneis, Alexander Langer, Peter Rossmanith: Derandomizing Non-uniform Color-Coding I

2009-08 Joachim Kneis, Alexander Langer: Satellites and Mirrors for Solving Independent Set on Sparse Graphs

2009-09 Michael Nett: Implementation of an Automated Proof for an Algorithm Solving the Maximum Independent Set Problem

2009-10 Felix Reidl, Fernando Sánchez Villaamil: Automatic Verification of the Correctness of the Upper Bound of a Maximum Independent Set Algorithm

2009-11 Kyriaki Ioannidou, George B. Mertzios, Stavros D. Nikolopoulos: The Longest Path Problem is Polynomial on Interval Graphs

2009-12 Martin Neuhäußer, Lijun Zhang: Time-Bounded Reachability in Continuous-Time Markov Decision Processes

2009-13 Martin Zimmermann: Time-optimal Winning Strategies for Poset Games

2009-14 Ralf Huuck, Gerwin Klein, Bastian Schlich (eds.): Doctoral Symposium on Systems Software Verification (DS SSV'09)

2009-15 Joost-Pieter Katoen, Daniel Klink, Martin Neuhäußer: Compositional Abstraction for Stochastic Systems

2009-16 George B. Mertzios, Derek G. Corneil: Vertex Splitting and the Recognition of Trapezoid Graphs

2009-17 Carsten Kern: Learning Communicating and Nondeterministic Automata

2009-18 Paul Hänsch, Michaela Slaats, Wolfgang Thomas: Parametrized Regular Infinite Games and Higher-Order Pushdown Strategies

2010-02 Daniel Neider, Christof Löding: Learning Visibly One-Counter Automata in Polynomial Time

2010-03 Holger Krahn: MontiCore: Agile Entwicklung von domänenspezifischen Sprachen im Software-Engineering

2010-04 René Wörzberger: Management dynamischer Geschäftsprozesse auf Basis statischer Prozessmanagementsysteme

2010-05 Daniel Retkowitz: Softwareunterstützung für adaptive eHome-Systeme

2010-06 Taolue Chen, Tingting Han, Joost-Pieter Katoen, Alexandru Mereacre: Computing maximum reachability probabilities in Markovian timed automata

2010-07 George B. Mertzios: A New Intersection Model for Multitolerance Graphs, Hierarchy, and Efficient Algorithms

2010-08 Carsten Otto, Marc Brockschmidt, Christian von Essen, Jürgen Giesl: Automated Termination Analysis of Java Bytecode by Term Rewriting

2010-09 George B. Mertzios, Shmuel Zaks: The Structure of the Intersection of Tolerance and Cocomparability Graphs

2010-10 Peter Schneider-Kamp, Jürgen Giesl, Thomas Ströder, Alexander Serebrenik, René Thiemann: Automated Termination Analysis for Logic Programs with Cut

2010-11 Martin Zimmermann: Parametric LTL Games

2010-12 Thomas Ströder, Peter Schneider-Kamp, Jürgen Giesl: Dependency Triples for Improving Termination Analysis of Logic Programs with Cut

2010-13 Ashraf Armoush: Design Patterns for Safety-Critical Embedded Systems

2010-14 Michael Codish, Carsten Fuhs, Jürgen Giesl, Peter Schneider-Kamp: Lazy Abstraction for Size-Change Termination

2010-15 Marc Brockschmidt, Carsten Otto, Christian von Essen, Jürgen Giesl: Termination Graphs for Java Bytecode

2010-16 Christian Berger: Automating Acceptance Tests for Sensor- and Actuator-based Systems on the Example of Autonomous Vehicles

2010-17 Hans Grönniger: Systemmodell-basierte Definition objektbasierter Modellierungssprachen mit semantischen Variationspunkten

2010-18 Ibrahim Armaç: Personalisierte eHomes: Mobilität, Privatsphäre und Sicherheit

2010-19 Felix Reidl: Experimental Evaluation of an Independent Set Algorithm

2010-20 Wladimir Fridman, Christof Löding, Martin Zimmermann: Degrees of Lookahead in Context-free Infinite Games

2011-02 Marc Brockschmidt, Carsten Otto, Jürgen Giesl: Modular Termination Proofs of Recursive Java Bytecode Programs by Term Rewriting

2011-03 Lars Noschinski, Fabian Emmes, Jürgen Giesl: A Dependency Pair Framework for Innermost Complexity Analysis of Term Rewrite Systems

2011-04 Christina Jansen, Jonathan Heinen, Joost-Pieter Katoen, Thomas Noll: A Local Greibach Normal Form for Hyperedge Replacement Grammars

2011-07 Shahar Maoz, Jan Oliver Ringert, Bernhard Rumpe: An Operational Semantics for Activity Diagrams using SMV

2011-08 Thomas Ströder, Fabian Emmes, Peter Schneider-Kamp, Jürgen Giesl, Carsten Fuhs: A Linear Operational Semantics for Termination and Complexity Analysis of ISO Prolog

2011-09 Markus Beckers, Johannes Lotz, Viktor Mosenkis, Uwe Naumann (Editors): Fifth SIAM Workshop on Combinatorial Scientific Computing

2011-10 Markus Beckers, Viktor Mosenkis, Michael Maier, Uwe Naumann: Adjoint Subgradient Calculation for McCormick Relaxations

2011-11 Nils Jansen, Erika Ábrahám, Jens Katelaan, Ralf Wimmer, Joost-Pieter Katoen, Bernd Becker: Hierarchical Counterexamples for Discrete-Time Markov Chains

2011-12 Ingo Felscher, Wolfgang Thomas: On Compositional Failure Detection in Structured Transition Systems

2011-13 Michael Förster, Uwe Naumann, Jean Utke: Toward Adjoint OpenMP

2011-14 Daniel Neider, Roman Rabinovich, Martin Zimmermann: Solving Muller Games via Safety Games

2011-16 Niloofar Safiran, Uwe Naumann: Toward Adjoint OpenFOAM

2011-18 Kamal Barakat: Introducing Timers to pi-Calculus

2011-19 Marc Brockschmidt, Thomas Ströder, Carsten Otto, Jürgen Giesl: Automated Detection of Non-Termination and NullPointerExceptions for Java Bytecode

2011-24 Callum Corbett, Uwe Naumann, Alexander Mitsos: Demonstration of a Branch-and-Bound Algorithm for Global Optimization using McCormick Relaxations

2011-25 Callum Corbett, Michael Maier, Markus Beckers, Uwe Naumann, Amin Ghobeity, Alexander Mitsos: Compiler-Generated Subgradient Code for McCormick Relaxations

* These reports are only available as a printed version.

Please contact `biblio@informatik.rwth-aachen.de` to obtain copies.